U.S. Department of Transportation

Federal Aviation Administration

**Transmittal Letter 20-21** 

August 21, 2020

## PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: \$97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; \$97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; \$97.27 NDB, NDB/DME; \$97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; \$97.31 RADAR SIAPs; \$97.33 RNAV SIAPs; and \$97.35 COPTER SIAPs, Identified as follows:

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/8/2020	ME	Augusta	Augusta State	0/4433	7/29/2020	RNAV (GPS) RWY 17, Orig-A

## **AIRAC Date: 8 OCTOBER 2020**

FDC 0/4433 AUG IAP AUGUSTA STATE, AUGUSTA, ME. RNAV (GPS) RWY 17, ORIG-A... CHART CIRCLING ICON. CIRCLING CAT D MDA 1160/HAA 808. VIS CAT D 2 1/2. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 900-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WATERVILLE ALTIMETER SETTING AND INCREASE ALL DA 35 FEET AND ALL MDA 40 FEET; INCREASE LNAV/VANV ALL CATS AND LNAV CATS C AND D VISIBILITY 1/8 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WATERVILLE ALTIMETER SETTING: INCREASE LPV DA TO 583 FEET, LNAV/VNAV DA TO 710 FEET, AND VISIBILITY LNAV/VNAV ALL CATS 1/8 SM; INCREASE ALL MDA 40 FEET AND VISIBILITY LNAV CATS C AND D 1/8 SM, AND CIRCLING CAT D 1/4 SM. THIS IS RNAV (GPS) RWY 17, ORIG-B. 2007241437-PERM