

**Federal Aviation
Administration**

Transmittal Letter 18-23

September 21, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
8-Nov-18	AR	Little Rock	Bill and Hillary Clinton National/Adams Field	8/4149	9/13/18	ILS OR LOC RWY 22R, ILS RWY 22R (SA CAT I), ILS RWY 22R (CAT II-III), Amdt 3

AIRAC Date: 8 NOVEMBER 2018

FDC **8/4149** LIT IAP BILL AND HILLARY CLINTON NATIONAL/ADAMS FIELD, Little Rock, AR. ILS OR LOC RWY 22R, AMDT 3... ILS RWY 22R (SA CAT I), AMDT 3... ILS RWY 22R (CAT II-III), AMDT 3... DELETE NOTE: ASR. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STUTTGART ALTIMETER SETTING: INCREASE ALL DA TO 544 FEET AND INCREASE S-ILS ALL CATS VISIBILITY TO RVR 2200; INCREASE ALL MDAS 100 FEET AND INCREASE S-LOC CAT C/D VISIBILITY TO RVR 5500, AND CIRCLING CAT B VISIBILITY TO 1-1/4 SM, CAT C VISIBILITY TO 3 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STUTTGART ALTIMETER SETTING AND INCREASE ALL DA TO 544 AND, INCREASE S-ILS ALL CATS VISIBILITY TO RVR 2200, ALL MDA 100 FEET AND INCREASE S-LOC CAT C/D VISIBILITY TO RVR 5500, AND CIRCLING CAT B VISIBILITY TO 1-1/4 MILE, CAT C VISIBILITY TO 3 MILES. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC CAT C/D VISIBILITY TO RVR 6000. DELETE NOTE: FOR INOPERATIVE ALSF-2, INCREASE S-LOC CAT C/D VISIBILITY TO RVR 6000. CHART NOTE: FOR INOPERATIVE ALS WHEN USING STUTTGART ALTIMETER SETTING, INCREASE S-ILS ALL CATS VISIBILITY TO RVR 4500 AND S-LOC CAT C/D VISIBILITY TO 1-3/8 SM. DELETE NOTE: FOR INOPERATIVE ALSF-2 WHEN USING STUTTGART ALTIMETER SETTING, INCREASE S-ILS ALL CATS VISIBILITY TO RVR 4500 AND S-LOC CAT C/D

VISIBILITY TO 1-3/8 MILE. PBN REQUIREMENTS NOTE: DME REQUIRED. DELETE PLANVIEW 3A, ILS RWY 22R (CAT II-III) NOTE: DME REQUIRED. THIS IS ILS OR LOC RWY 22R, AMDT 3A, ILS RWY 22R (SA CAT I), AMDT 3A, ILS RWY 22R (CAT II-III) AMDT 3A. 1809051924-PERM