



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

\*LNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE IOWA CITY ALTIMETER SETTING AND INCREASE ALL DA 64 FEET AND ALL MDA 80 FEET; INCREASE LNAV/VNAV ALL CATS VISIBILITY TO RVR 5000 AND LNAV CAT C TO RVR 4000.

CHART NOTE: FOR INOPERATIVE MALSR INCREASE LNAV CAT D VISIBILITY TO RVR 6000.

CHART NOTE: VDP NA WITH IOWA CITY ALTIMETER SETTING.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT VINTY ON V67 NORTHWEST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT GUERN ON V294 SOUTHWEST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT BEIGE ON V172 WESTBOUND.

CHART NOTE: WHEN USING IOWA CITY ALTIMETER SETTING; FOR INOPERATIVE MALSR, INCREASE LPV ALL CATS VISIBILITY TO RVR 5000, LNAV CAT C VISIBILITY TO RVR 6000 AND LNAV CAT D VISIBILITY TO 1 1/2 MILES.



CITY AND STATE CEDAR RAPIDS, IA	ELEVATION: 870 TDZE: 857 AIRPORT NAME: THE EASTERN IOWA	FACILITY IDENTIFIER: RNAV	PROCEDURE NO / AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 2, 09/23/2010 23 SEP 2010	SUP:
				AMDT: 1
				DATED: 05/10/2007

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCID
RUNWAY	RW09
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W09A
LTP/FTP LATITUDE	415304.7385N
LTP/FTP LONGITUDE	0914345.0070W
LTP/FTP ELLIPSOIDAL HEIGHT	+02281
FPAP LATITUDE	415303.3800N
FPAP LONGITUDE	0914151.3300W
THRESHOLD CROSSING HEIGHT (TCH)	00049.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

**CRC REMAINDER** F416E475

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+02603
FPAP ORTHOMETRIC HEIGHT	+02603

QUALITY  
5  
CHECKED

CITY AND STATE CEDAR RAPIDS, IA	ELEVATION: 870 TDZE: 857 AIRPORT NAME: THE EASTERN IOWA	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 2, 09/23/2010 23 SEP 2010	SUP:
				AMDT: 1
				DATED: 05/10/2007



