

QUALITY
Cycles

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	157/30 CW 337/30 (NOPT)	157/10 CW 337/10	6700
2.	157/10 CW 337/10	PULAE (IF/IAF) (FB)	6300
3.	337/30 CW 157/30	337/10 CW 157/10	7700
4.	337/10 CW 157/10	PULAE (IF/IAF) (FO)	6300

QUALITY
9
CHECKED

CITY AND STATE
ROUNDUP, MT

ELEVATION: 3490 THRE: 3431
AIRPORT NAME:
ROUNDUP

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 25, ORIG
20 SEPTEMBER 2012

SUP:
AMDT: NONE
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRPX
RUNWAY	RW25
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W25A
LTP/FTP LATITUDE	462835.6490N
LTP/FTP LONGITUDE	1083153.7260W
LTP/FTP ELLIPSOIDAL HEIGHT	+10324
FPAP LATITUDE	462816.7300N
FPAP LONGITUDE	1083359.7100W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1200
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

013173DD

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K1
LTP ORTHOMETRIC HEIGHT	+10456
FPAP ORTHOMETRIC HEIGHT	+10456

CITY AND STATE

ROUNDUP, MT

ELEVATION: 3490

THRE: 3431

AIRPORT NAME:

ROUNDUP

 FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 25, ORIG

20 SEPTEMBER 2012

SUP:

AMDT: NONE

DATED:

 QUALITY
9
CHECKED

FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18 - RNAV (GPS)

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KRPXK1FR25	APULAE	010PULA	AEK1EA0EE	AR	HF	24700070	+	06300	18000		A	JS
SUSAP	KRPXK1FR25	R	010PULA	AEK1EA0E	I	IF		+	06300	18000		A	JS
SUSAP	KRPXK1FR25	R	020LUNNAK1EA1E	F	051TF		24700074	+	05200			A	JS
SUSAP	KRPXK1FR25	R	020LUNNAK1EA2WALPV			ALNAV/VNAV						JS	
SUSAP	KRPXK1FR25	R	030RW25	K1PGOGY	M	031TF	24680054		03476	-300		A	JS
SUSAP	KRPXK1FR25	R	040		0	M	2468	+	03746			A	JS
SUSAP	KRPXK1FR25	R	050SWIVLK1EA0EY		DF			+	06600			A	JS
SUSAP	KRPXK1FR25	R	060SWIVLK1EA0EE	R	HM		06650070	+	06600			A	JS

[illegible][illegible]

CITY AND STATE
ROUNDUP, MT

ELEVATION: 3490
AIRPORT NAME:

THRE: 3431

FACILITY
IDENTIFIER:

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 25, ORIG
 20 SEPTEMBER 2012

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	PULAE	PULAE	010	IAF	HF	R	FO		247.0 (258.0T)	007.0	AA 06300	
		PULAE	010	FACF	IF		FB				AA 06300	
		LUNNA	020	FAF	TF		FB	0.5	247.0 (258.0T)	007.4	AA 05200	
		RW25	030	MAP	TF		FO	0.3	246.8 (257.8T)	005.4	AT 03476	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		246.8 (257.8T)		AA 03746	
	SWIVL	050		DF		FO				AA 06600	
	SWIVL	060		HM	R	FO		066.5 (077.5T)	007.0	AA 06600	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	LUNNA	N462944.30	W1082414.20	N4629.738	W10824.237
	PULAE	N463117.23	W1081346.02	N4631.287	W10813.767
	SWIVL	N462541.29	W1085104.78	N4625.688	W10851.080
	RW25	N462835.65	W1083153.73	N4628.594	W10831.896

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW25	03431	45

QUALITY
CHECKED

CITY AND STATE ROUNDUP, MT	ELEVATION: 3490 THRE: 3431	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 25, ORIG 20 SEPTEMBER 2012	SUP:
	AMDT: NONE			
	DATED:			