

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KBCR	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 1	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> BONIFAY	<u>STATE</u> FL		
<u>AIRPORT ELEVATION</u> 86	<u>TDZE</u> 86	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>MAG VAR</u> 3W	<u>EPOCH YEAR</u> 2010
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 2 DECEMBER 2021	<u>REQUIRED EFFECTIVE DATE</u> 12/02/2021	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
MAI VORTAC		BAYNA		TF	FB	1.00	245.47	20.01	2000
LAARA		PIHOD		TF	FB	1.00	145.57	9.59	2000
BAYNA	IAF	ADUBY	NOPT	TF	FB	1.00	282.76	9.00	2000
PIHOD	IAF	ADUBY	NOPT	TF	FB	1.00	102.58	9.00	2000
ADUBY	IF	QUITR		TF	FB	1.00	012.65	6.28	1700
QUITR	FAF	FEZEK/1.30 NM TO RW1		TF	FB	0.30	012.66	3.35	
FEZEK/1.30 NM TO RW1		RW1	MAP	TF	FO	0.30	012.66	1.30	
RW1	MAP	700 MSL		CA			012.66		700
700 MSL		BJLEW		DF	FO	1.00			2000

MISSED APPROACH

MAP:

LPV: DA
LNAV/VNAV: DA
LNAV: RW1

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 700 THEN CLIMBING RIGHT TURN TO 2000 DIRECT BJLEW AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

QUALITY
8
CHECKED

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. PROFILE STARTS AT ADUBY

3. FAC: 012.66 FAF: QUITR DIST FAF TO MAP: 4.65 DIST FAF TO THLD: 4.65

4. MIN ALT: ADUBY 2000, QUITR 1700, FEZEK/1.30 NM TO RW1 580

5. DIST TO THLD FROM PFAF: 4.65 MM: IM: 150 HAT: 329 HAT: 0.80 GS ANT:

6. MIN GP INCPT: 1700 GP ALT AT PFAF : QUITR 1700 OM: MM: IM:

7. GP ANGLE: 3.15 34:1: IS NOT CLEAR 20:1: IS CLEAR TCH: 60.0

8. MSA FROM: RW01 3100

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART NOTE: BARO-VNAV NA WHEN USING MARIANNA ALTIMETER SETTING.
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
CHART NOTE: CIRCLING RWY 19 NA AT NIGHT.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MARIANNA ALTIMETER SETTING: INCREASE LPV DA TO 468 AND LNAV/VNAV DA TO 573 AND ALL VISIBILITIES 1/8 SM;
INCREASE ALL MDAS 60 FEET AND VISIBILITY CAT C 1/4 SM.

ADDITIONAL FLIGHT DATA:

299 AAO 304536N/0853746W.
HOLD W, LT, 092.10 INBOUND.
FAS OBST: 259 TREE 305034N/0853649W.
WAAS CHANNEL # 99344
REFERENCE PATH ID: W01A
CHART CIRCLING ICON.
LTP HAE: -1.6 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LPV DA	415	1	329	415	1	329	415	1	329		NA				
LNAV/VNAV DA	520	1 1/4	434	520	1 1/4	434	520	1 1/4	434		NA				
LNAV MDA	520	1	434	520	1	434	520	1 1/4	434		NA				
CIRCLING	580	1	494	600	1	514	680	1 1/2	594		NA				



CHANGES - REASONS

COORDINATED WITH:

A4A ☐ **ALPA** ☒ **AOPA** ☒ **APA** ☐ **HAI** ☐ **NBAA** ☒ **OTHER:** ZJX, CAIRNS APP CON, AMGR.

FLIGHT CHECKED BY
PENDING

Digitally signed by
JON DENTON
Oct 04, 2021

OFFICE

DATE

DEVELOPED BY *Digitally signed by*
VICTOR BOONE **VICTOR C BOONE**
Sep 23, 2021

OFFICE
AJV-A432

DATE

APPROVED BY
LONNIE EVERHART

Digitally signed by
JON DENTON
Oct 04, 2021

OFFICE
AJV-A430

DATE

TITLE
MANAGER



FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBCR
RUNWAY	RW01
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W01A
LTP/FTP LATITUDE	305011.6540N
LTP/FTP LONGITUDE	0853611.4985W
LTP/FTP ELLIPSOIDAL HEIGHT	-00016
FPAP LATITUDE	305139.6880N
FPAP LONGITUDE	0853554.1080W
THRESHOLD CROSSING HEIGHT (TCH)	00060.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.15
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1104
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
CRC REMAINDER	0C50D980

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00262
FPAP ORTHOMETRIC HEIGHT	+00262

