U.S. Department of Transportation

Federal Aviation Administration

Transmittal Letter 22-22

September 2, 2022

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVEUPONPUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/6/2022	ОН	Marysville	Union County	2/0537	8/23/2022	RNAV (GPS) RWY 9, Orig-A

AIRAC Date: 6 OCTOBER 2022

FDC 2/0537 MRT IAP UNION COUNTY, MARYSVILLE, OH. RNAV (GPS) RWY 9, ORIG-A... CIRCLING CAT C/D MDA 1620/HAA 599. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JOHN GLENN COLUMBUS INTL ALTIMETER SETTING AND INCREASE ALL MDAS 100 FEET; INCREASE LP VISIBILITY CAT C/D 1/4 SM, LNAV VISIBILITY CAT C/D 3/8 SM, AND CIRCLING VISIBILITY CAT C/D 1/2 SM. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT. CHANGE NOTE TO READ: RWY 9 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NA. CHART NOTE: WHEN CIRCLING TO RWY 27 AT NIGHT, OPERATIONAL VGSI REQUIRED, REMAIN ON OR ABOVE VGSI GLIDEPATH UNTIL THRESHOLD. THIS IS RNAV (GPS) RWY 9, ORIG-B. 2208161543-PERM