

**Federal Aviation
Administration**

Transmittal Letter 25-02

November 22, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/26/2024	ME	Presque Isle	Presque Isle Intl	4/1152	11/8/2024	RNAV (GPS) RWY 28, Amdt 2

AIRAC Date: 26 DECEMBER 2024

FDC 4/1152 PQI IAP PRESQUE ISLE INTL, PRESQUE ISLE, ME. RNAV (GPS) RWY 28, AMDT 2... LNAV/VNAV DA 1085/HAT 612 ALL CATS. CIRCLING CAT C MDA 1320/HAA 786, CIRCLING CAT D MDA 1380/HAA 846. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH - GPS. CHART NOTE: CIRCLING RWY 10 NA AT NIGHT. CHART NOTE: RWY 28 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE ASTERISK FROM MINIMUM ALTITUDE AT PESIC/2.64 NM TO RW28 1340. DELETE ASTERISK FROM VDP AT 1.57 NM TO RW28. DELETE PROFILE NOTE: *LNAV ONLY. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HUL ALTIMETER SETTING: INCREASE LPV DA TO 855 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE LNAV/VNAV DA TO 1175 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CATS C AND D 1/4 SM, AND CIRCLING VISIBILITY CAT C 1/2 SM AND CAT D 1/4 SM. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING HUL ALTIMETER SETTING. CHANGE ALTERNATE MINIMUMS NOTE TO READ: STANDARD - CAT C 800-2 1/4, CAT D 900-2 3/4- NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 28, AMDT 2A. 2411081251-PERM