

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
MILUM INT/BDR 5.00 DME	BDR VOR/DME	233.92 / 5.00	1800
BDR VOR/DME	STANE INT/I-BDR 6.23 DME	239.68 / 5.87	1800
CCC VOR/DME	STANE INT/I-BDR 6.23 DME	310.50 / 21.55	1800

ILS: DA
LOC: 5.47 NM AFTER STANE INT/I-BDR 6.23 DME OR AT I-BDR 0.76 DME

CLIMB TO 1800 ON THE BDR VOR/DME R-054 TO MILUM INT AND HOLD.

ALTERNATE MA (DO NOT CHART): CLIMB TO 500 THEN CLIMBING RIGHT TURN TO 2000 DIRECT CCC VOR/DME AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD NE, RT, 233.92 INBOUND.
FAS OBST: 125 SHIP 410800N/0730930W
CHART VDP AT 1.77 DME*
DISTANCE VDP TO THLD 1.01 NM.
*LOC ONLY.
CHART CIRCLING ICON.
FICTITIOUS THRESHOLD POINT (CFLVP) DO NOT CHART.
CHART: (CFVFS) 410055.17N/0731959.38W.
FAC CROSSES RWY C/L EXTENDED 2691 FT FROM THLD.
CHART PLANVIEW NOTE: FINAL APPROACH COURSE OFFSET 2.16 DEGREES.

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SW STANE, RT, 060.16 INBOUND, 1800 FT. IN LIEU OF PT (IAF)
- FAC: 060.16 FAF: STANE INT/I-BDR 6.23 DME DIST FAF TO MAP: 5.47 THLD: 5.47
- MIN. ALT: STANE 1800
- DIST TO THLD FROM OM: - MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: 992
- MIN GS INCPT: 1800 GS ALT AT: STANE 1800 OM: - MM: - IM: -
- GS ANGLE: 3.00 TCH: 50.5
- MSA FROM: BDR VOR/DME 360-090 2700, 090-270 1900, 270-360 2300

MAG VAR: 13W EPOCH YEAR: 1980

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			ILS: STANDARD #			LOC: STANDARD @		
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 06	257	3/4	250	257	3/4	250	257	3/4	250	257	3/4	250			
S-LOC 06	380	1	373	380	1	373	380	1	373	380	1	373			
CIRCLING	400	1	391	620	1	611	820	2 1/2	811	820	2 3/4	811			

NOTES:
CHART NOTE: CIRCLING TO RWY 11 NA AT NIGHT.

#@ NA WHEN CONTROL TOWER CLOSED.
CAT B 700-2, CAT C 900-2 1/2, CAT D 900-2 3/4
@ CAT C 900-2 1/2, CAT D 900-2 3/4



CITY AND STATE BRIDGEPORT, CT	ELEVATION: 9 TDZE: 7 AIRPORT NAME: IGOR I SIKORSKY MEMORIAL	FACILITY IDENTIFIER: I-BDR	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 6, AMDT 10 22 JUNE 2017	SUP: ILS RWY 6 AMDT: 9A DATED 07/10/2003
----------------------------------	---	-------------------------------	---	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE BRIDGEPORT, CT	ELEVATION: 9 AIRPORT NAME: IGOR I SIKORSKY MEMORIAL	TDZE: 7	FACILITY IDENTIFIER: I-BDR	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 6, AMDT 10 22 JUNE 2017	SUP: ILS RWY 6
					AMDT: 9A
					DATED: 07/10/2003