

**Federal Aviation
Administration**

Transmittal Letter 21-25

October 15, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/2/2021	KS	Great Bend	Great Bend Muni	1/8613	7/20/2021	RNAV (GPS) RWY 35, Orig-A

AIRAC Date: 2 DECEMBER 2021

FDC 1/8613 GBD IAP GREAT BEND MUNI, GREAT BEND, KS. RNAV (GPS) RWY 35, ORIG-A... CIRCLING CAT A MDA 2320/HAA 433, CAT C MDA 2520/HAA 633, CAT D MDA 2640/HAA 753. CIRCLING CAT C VISIBILITY 1 3/4, CAT D VISIBILITY 2 1/2. CHANGE BACKUP ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE RUSSELL MUNI ALTIMETER SETTING: INCREASE LPV DA TO 2248 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE LNAV/VNAV DA TO 2299 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 80 FEET AND VISIBILITY CATS C AND D 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 35, ORIG-B. 2107131830-PERM