

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

DP NAME	NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
EXTAN	SIX	EXTAN6.SHAYK	FIVE	07/11/2018	30 JAN 2020
TYPE:	OBSTACLE	COPTER	SID	SPECIAL	RNAV
	☐	☐	☒	☐	☒

DP ROUTE DESCRIPTION: DENVER INTL:

TAKEOFF RWY 8: CLIMB ON HEADING 082.53 TO INTERCEPT COURSE 105.56 TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 083.54 TO KMBEL, THEN ON TRACK 090.29 TO BHIGH, THEN ON TRACK 089.85 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

TAKEOFF RWY 16L: CLIMB ON HEADING 172.51 TO INTERCEPT COURSE 117.93 TO CROSS GISTT AT OR ABOVE 7000, THEN ON TRACK 081.07 TO CROSS BGONE AT OR BELOW 10000, THEN ON TRACK 082.43 TO OLDDD, THEN ON TRACK 082.62 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

TAKEOFF RWY 16R: CLIMB ON HEADING 172.51 TO INTERCEPT COURSE 117.93 TO CROSS GISTT AT OR ABOVE 7000, THEN ON TRACK 081.07 TO CROSS BGONE AT OR BELOW 10000, THEN ON TRACK 082.43 TO OLDDD, THEN ON TRACK 082.62 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

TAKEOFF RWY 17L: CLIMB ON HEADING 172.54 TO INTERCEPT COURSE 127.46 TO CROSS GISTT AT OR ABOVE 7000, THEN ON TRACK 081.07 TO CROSS BGONE AT OR BELOW 10000, THEN ON TRACK 082.43 TO OLDDD, THEN ON TRACK 082.62 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

TAKEOFF RWY 17R: CLIMB ON HEADING 172.53 TO INTERCEPT COURSE 117.95 TO CROSS GISTT AT OR ABOVE 7000, THEN ON TRACK 081.07 TO CROSS BGONE AT OR BELOW 10000, THEN ON TRACK 082.43 TO OLDDD. THEN ON TRACK 082.62 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

TAKEOFF RWY 25: CLIMB ON HEADING 262.51 TO 5934, THEN CONTINUE CLIMB ON HEADING 262.51 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO EXTAN, THENCE ...

TAKEOFF RWY 34L: CLIMB ON HEADING 352.51 TO 5934, THEN CLIMBING RIGHT TURN DIRECT TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 083.54 TO KMBEL, THEN ON TRACK 090.29 TO BHIGH, THEN ON TRACK 089.85 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

TAKEOFF RWY 34R: CLIMB ON HEADING 352.51 TO 5934, THEN CLIMBING RIGHT TURN DIRECT TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 083.54 TO KMBEL, THEN ON TRACK 090.29 TO BHIGH, THEN ON TRACK 089.85 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

TAKEOFF RWY 35L: CLIMB ON HEADING 352.53 TO 5934, THEN CLIMBING RIGHT TURN DIRECT TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 083.54 TO KMBEL, THEN ON TRACK 090.29 TO BHIGH, THEN ON TRACK 089.85 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

TAKEOFF RWY 35R: CLIMB ON HEADING 352.54 TO 5934, THEN CLIMBING RIGHT TURN DIRECT TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 083.54 TO KMBEL, THEN ON TRACK 090.29 TO BHIGH, THEN ON TRACK 089.85 TO CROSS MMESA AT OR ABOVE 14000, THENCE ...

... ON DEPICTED ROUTE TO SHAYK, MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

CENTENNIAL:

TAKEOFF RWY 17L, 17R: CLIMB ON HEADING 169.95 TO 6400, THEN CONTINUE CLIMB ON HEADING 169.95 OR AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 35L, 35R: CLIMB ON HEADING 349.95 TO 6400, THEN CONTINUE CLIMB ON HEADING 349.95 OR AS ASSIGNED BY ATC, THENCE ...

... RADAR VECTORS TO EXTAN, THEN ON DEPICTED ROUTE TO SHAYK. MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

ROCKY MOUNTAIN METROPOLITAN:



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
EXTAN	SIX	EXTAN6.SHAYK	FIVE	07/11/2018	

30 JAN 2020

TAKEOFF RWY 12L, 12R: CLIMB ON HEADING BETWEEN 150 CCW 350 AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 30L, 30R: CLIMBING RIGHT TURN HEADING BETWEEN 350 CW 113 AS ASSIGNED BY ATC. THENCE ...

... RADAR VECTORS TO EXTAN, THEN ON DEPICTED ROUTE TO SHAYK. MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

NORTHERN COLORADO RGNL:

TAKEOFF RWY 15: CLIMB ON HEADING BETWEEN 180 CCW 350 AS ASSIGNED BY ATC. THENCE ...

TAKEOFF RWY 33: CLIMBING RIGHT TURN HEADING BETWEEN 350 CW 150 AS ASSIGNED BY ATC, THENCE ...

... RADAR VECTORS TO EXTAN, THEN ON DEPICTED ROUTE TO SHAYK. MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

COLORADO AIR AND SPACE PORT:

TAKEOFF RWY 8: CLIMB ON HEADING 083.15 TO 6020, THEN CONTINUE CLIMB ON HEADING 083.15 OR AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 17: CLIMB ON HEADING 171.99 TO 6020, THEN CONTINUE CLIMB ON HEADING 171.99 OR AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 26: CLIMB ON HEADING 263.17 TO 6020, THEN CONTINUE CLIMB ON HEADING 263.17 OR AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 35: CLIMB ON HEADING 351.99 TO 6020, THEN CONTINUE CLIMB ON HEADING 351.99 OR AS ASSIGNED BY ATC, THENCE ...

... RADAR VECTORS TO EXTAN, THEN ON DEPICTED ROUTE TO SHAYK. MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:

NOTE: DME/DME/IRU OR GPS REQUIRED.

NOTE: RNAV 1.

NOTE: TURBOJETS ONLY.

NOTE: DENVER INTL AIRPORT-TAKEOFF RWY 8, 16L, 16R, 17L, 17R, 34L, 34R, 35L, 35R - RADAR REQUIRED FOR NON GPS EQUIPPED AIRCRAFT.

NOTE: DENVER INTL AIRPORT- RWY 25 DEPARTURES- RADAR REQUIRED.

NOTE: ROCKY MOUNTAIN METROPOLITAN AIRPORT, NORTHERN COLORADO RGNL, COLORADO AIR AND SPACE PORT AND CENTENNIAL AIRPORT- RADAR REQUIRED.

NOTE: ACCELERATE TO AT OR ABOVE 250 KNOTS ABOVE 10000. IF SLOWER SPEED IS REQUIRED TO MEET CROSSING RESTRICTIONS ADVISE CLNC DEL PRIOR TO TAXI.

NOTE: FOR NON GPS EQUIPPED AIRCRAFT TXC DME MUST BE OPERATIONAL.

TAKEOFF MINIMUMS:

DENVER INTL:

RWY 7, 26: NA- ATC.

RWY 8: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 5934 THEN MINIMUM CLIMB OF 260 FT PER NM TO 14000.

RWY 16L: STANDARD WITH MINIMUM CLIMB OF 245 FT PER NM TO 14000.

RWY16R: STANDARD WITH MINIMUM CLIMB OF 450 FT PER NM TO 5934 THEN MINIMUM CLIMB OF 225 FT PER NM TO 14000.

RWY 17L: STANDARD WITH MINIMUM CLIMB OF 465 FT PER NM TO 5934 THEN MINIMUM CLIMB OF 280 FT PER NM TO 14000.

RWY 17R: STANDARD WITH MINIMUM CLIMB OF 465 FT PER NM TO 5934 THEN MINIMUM CLIMB OF 250 FT PER NM TO 14000.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
EXTAN	SIX	EXTAN6.SHAYK	FIVE	07/11/2018	

30 JAN 2020

RWY 25: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 5934.
RWY 34L: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 5934 THEN MINIMUM CLIMB OF 220 FT PER NM TO 14000.
RWY 34R: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 5934 THEN MINIMUM CLIMB OF 230 FT PER NM TO 14000.
RWY 35L: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 5934 THEN MINIMUM CLIMB OF 240 FT PER NM TO 14000.
RWY 35R: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 5934 THEN MINIMUM CLIMB OF 240 FT PER NM TO 14000.

CENTENNIAL:

RWY 10, 28: NA - ATC.
RWY 35L, 35R: STANDARD.
RWY 17L: STANDARD WITH MINIMUM CLIMB OF 255 FT PER NM TO 8000.
RWY 17R: STANDARD WITH MINIMUM CLIMB OF 370 FT PER NM TO 8000.

ROCKY MOUNTAIN METROPOLITAN:

RWY 3, 21: NA - ATC.
RWY 12L, 12R, 30L, 30R: STANDARD.

NORTHERN COLORADO RGNL:

RWY 6, 24: NA - VFR RUNWAY.
RWY 15, 33: STANDARD.

COLORADO AIR AND SPACE PORT:

RWY 8, 17, 26, 35: STANDARD.

TAKEOFF OBSTACLES NOTES:

DENVER INTL:
 SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

ROCKY MOUNTAIN METROPOLITAN:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CENTENNIAL:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

NORTHERN COLORADO RGNL:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

COLORADO AIR AND SPACE PORT:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

CENTENNIAL:
RWY 17L: 6559 FT MSL AAO 392953.93N/1045044.26W.
RWY 17R: 6021 FT MSL OBS LT ON BLDG 393302.52N/1045119.43W, 6559 FT MSL AAO 392953.93N/1045044.26W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KDEN 8E EPOCH YR: 2015.
DME ASSESSMENT: SAT (RNP 2.0).
ALL AIRPORTS - CHART: TOP ALTITUDE: FL230.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
EXTAN	SIX	EXTAN6.SHAYK	FIVE	07/11/2018	30 JAN 2020

PILOT NAVIGATION AREA:

10 NM ARC CENTERED ON EXTAN (IF), CW
FROM: POINT A (BEARING 043 DEGREES TO EXTAN)
TO: POINT B (BEARING 132 DEGREES TO EXTAN)
MINIMUM ALTITUDE - 14000

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
DENVER INTL (KDEN)	DENVER	CO
CENTENNIAL (KAPA)	DENVER	CO
ROCKY MOUNTAIN METROPOLITAN (KBJC)	DENVER	CO
NORTHERN COLORADO RGNL (KFNL)	FORT COLLINS/LOVELAND	CO
COLORADO AIR AND SPACE PORT (KCFO)	DENVER	CO

COMMUNICATIONS:

DENVER INTL: D-ATIS DEP, CLNC DEL, CPDLC, DEN DEP CON
CENTENNIAL AIRPORT: ATIS, CLNC DEL, DEN DEP CON
ROCKY MOUNTAIN METROPOLITAN: ATIS, CLNC DEL, DEN DEP CON
NORTHERN COLORADO RGN: DEN DEP CON
COLORADO AIR AND SPACE PORT: ATIS, CLNC DEL, DEN DEP CON, DEN CLNC DEL (WHEN TOWER CLOSED)

FIXES AND/OR NAVAIDS:

REMARKS:

ABBREVIATED AMENDMENT

CLIMB GRADIENTS AT CENTENNIAL OFF RWY 17L/R ARE OBSTACLE DRIVEN WITH THE CLIMB TO ALTITUDE DETERMINED BY LOCATION OF 8000 MVA AND PROXIMITY TO HIGHER MVA'S.

DENVER INTL CLIMB GRADIENTS ARE FOR FMS ENGAGEMENT AT SPECIFIC LOCATIONS AND FOR WP CROSSING RESTRICTIONS.

THE AIRLINE INDUSTRY HAS REQUESTED THAT BLOCK ALTITUDES NOT BE PUBLISHED ON THE PROCEDURE, WAIVER ON FILE TO REMOVE AT/ABOVE ALTITUDES ASSOCIATED WITH CROSS AT OR BELOW ALTITUDES.

ATC HAS REQUESTED TO DEVIATE FROM THE STANDARD NAMING CONVENTION CONTAINED IN FAAO 8260.46. SID NAMES CORRESPOND WITH WAYPOINT NAMES AT OUTER BOUNDARY OF DENVER TRACON/ARTCC AIRSPACE. WAIVER APPROVED AND ON FILE



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
EXTAN	SIX	EXTAN6.SHAYK	FIVE	07/11/2018	

30 JAN 2020

FLIGHT INSPECTED BY:

PROCESSED IAW AIRCRAFT OPS GRP (AJW-33) MEMO,
10/3/18, SUB: FLIGHT INSPECTION REVIEW NOT REQUIRED

Digitally signed by

ALLAN WILL

Dec 04, 2019

OFFICE SYMBOL:

DATE:

DEVELOPED BY:

PHILLIP BRANDENBURG

Digitally signed by

PHILLIP BRANDENBURG

Aug 20, 2019

OFFICE SYMBOL:

DATE:

AJV-A423

08/19/2019

APPROVED BY:

MARLON ROBINSON

Digitally signed by

ALLAN WILL

Dec 04, 2019

OFFICE SYMBOL:

DATE:

AJV-A420

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A ALPA AOPA APA HAI NBAA

☒ ☒ ☒ ☒ ☐ ☒

OTHER:

ZDV, BJC ATCT, DEN APP CON, CO AERO MGR, APT MGR'S

CHANGES - REASONS:

1. CHANGED ALL AIRPORT NAME REFERENCES FROM FRONT RANGE TO COLORADO AIR AND SPACE PORT, ID CHANGED FROM KFTG TO KCFO - PER FPT/APT REQUEST.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
EXTAN		SIX		EXTAN6.SHAYK		FIVE		07/11/2018	30 JAN 2020
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
DENVER INTL (KDEN)									
RW08 (AER)	395239.20N/1043944.03W	N	-	-	-	-			CG 500 FT PER NM TO 5934 THEN CG 260 FT PER NM TO 14000
	395237.36N/1043530.40W	-	-	VI	090.53	3.25			RECOMMENDED NAVAID: DENVER VOR/DME.
KIDNG	394837.67N/1042339.58W	Y	FB	CF	113.56	9.96	AT/BELOW 10000		
KMBEL	394832.93N/1041954.44W	Y	FB	TF	091.54	2.89			
BHIGH	394717.15N/1040845.34W	Y	FB	TF	098.29	8.69			
MMESA	394553.28N/1035543.50W	Y	FB	TF	097.85	10.14	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
RW16L (AER)	395349.33N/1044112.50W	N	-	-	-	-			CG 245 FT PER NM TO 14000
	394927.09N/1044115.54W	-	-	VI	180.51	4.37			RECOMMENDED NAVAID: DENVER VOR/DME.
GISTT	394557.50N/1043501.10W	Y	FB	CF	125.93	5.94	AT/ABOVE 7000		
BGONE	394606.21N/1042232.94W	Y	FB	TF	089.07	9.62	AT/BELOW 10000		
OLDDD	394600.62N/1040849.64W	Y	FB	TF	090.43	10.58			
MMESA	394553.28N/1035543.50W	Y	FB	TF	090.62	10.10	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
RW16R (AER)	395344.87N/1044145.90W	N	-	-	-	-			CG 450 FT PER NM 5934 THEN CG 225 FT PER NM TO 14000
	394945.61N/1044148.66W	-	-	VI	180.51	3.98			RECOMMENDED NAVAID: DENVER VOR/DME.
GISTT	394557.50N/1043501.10W	Y	FB	CF	125.93	6.47	AT/ABOVE 7000		



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
EXTAN		SIX		EXTAN6.SHAYK		FIVE		07/11/2018	30 JAN 2020
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
BGONE	394606.21N/1042232.94W	Y	FB	TF	089.07	9.62	AT/BELOW 10000		
OLDDD	394600.62N/1040849.64W	Y	FB	TF	090.43	10.58			
MMESA	394553.28N/1035543.50W	Y	FB	TF	090.62	10.10	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
RW17L (AER)	395153.83N/1043828.70W	N	-	-	-	-			CG 465 FT PER NM TO 5934 THEN CG 280 FT PER NM TO 14000
	394842.01N/1043831.06W	-	-	VI	180.54	3.19			RECOMMENDED NAVAID: DENVER VOR/DME.
GISTT	394557.50N/1043501.10W	Y	FB	CF	135.46	3.84	AT/ABOVE 7000		
BGONE	394606.21N/1042232.94W	Y	FB	TF	089.07	9.62	AT/BELOW 10000		
OLDDD	394600.62N/1040849.64W	Y	FB	TF	090.43	10.58			
MMESA	394553.28N/1035543.50W	Y	FB	TF	090.62	10.10	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
RW17R (AER)	395140.48N/1043936.56W	N	-	-	-	-			CG 465 FT PER NM TO 5934 THEN CG 250 FT PER NM TO 14000
	394833.02N/1043938.81W	-	-	VI	180.53	3.12			RECOMMENDED NAVAID: DENVER VOR/DME.
GISTT	394557.50N/1043501.10W	Y	FB	CF	125.95	4.41	AT/ABOVE 7000		
BGONE	394606.21N/1042232.94W	Y	FB	TF	089.07	9.62	AT/BELOW 10000		
OLDDD	394600.62N/1040849.64W	Y	FB	TF	090.43	10.58			
MMESA	394553.28N/1035543.50W	Y	FB	TF	090.62	10.10	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
EXTAN		SIX		EXTAN6.SHAYK		FIVE		07/11/2018	30 JAN 2020
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
RW25 (AER)	395026.37N/1044102.17W	N	-	-	-	-			CG 400 FT PER NM TO 5934
5934 MSL	-	-	-	VA	270.51	-			
	-	-	-	VM	270.51	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			LEFT TURN
RW34L (AER)	395106.79N/1044147.72W	N	-	-	-	-			CG 500 FT PER NM TO 5934 THEN 220 FT PER NM TO 14000
5934 MSL	-	-	-	VA	000.51	-			
KIDNG	394837.67N/1042339.58W	Y	FB	DF	-	-	AT/BELOW 10000		
KMBEL	394832.93N/1041954.44W	Y	FB	TF	091.54	2.89			
BHIGH	394717.15N/1040845.34W	Y	FB	TF	098.29	8.69			
MMESA	394553.28N/1035543.50W	Y	FB	TF	097.85	10.14	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
RW34R (AER)	395150.77N/1044113.88W	N	-	-	-	-			CG 500 FT PER NM TO 5934 THEN 230 FT PER NM TO 14000
5934 MSL	-	-	-	VA	000.51	-			
KIDNG	394837.67N/1042339.58W	Y	FB	DF	-	-	AT/BELOW 10000		
KMBEL	394832.93N/1041954.44W	Y	FB	TF	091.54	2.89			
BHIGH	394717.15N/1040845.34W	Y	FB	TF	098.29	8.69			
MMESA	394553.28N/1035543.50W	Y	FB	TF	097.85	10.14	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
EXTAN		SIX		EXTAN6.SHAYK		FIVE		07/11/2018	30 JAN 2020
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
RW35L (AER)	394941.93N/1043937.98W	N	-	-	-	-			CG 500 FT PER NM TO 5934 THEN 240 FT PER NM TO 14000
5934 MSL	-	-	-	VA	000.53	-			
KIDNG	394837.67N/1042339.58W	Y	FB	DF	-	-	AT/BELOW 10000		
KMBEL	394832.93N/1041954.44W	Y	FB	TF	091.54	2.89			
BHIGH	394717.15N/1040845.34W	Y	FB	TF	098.29	8.69			
MMESA	394553.28N/1035543.50W	Y	FB	TF	097.85	10.14	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
RW35R (AER)	394955.27N/1043830.16W	N	-	-	-	-			CG 500 FT PER NM TO 5934 THEN 240 FT PER NM TO 14000
5934 MSL	-	-	-	VA	000.54				
KIDNG	394837.67N/1042339.58W	Y	FB	DF	-	-	AT/BELOW 10000		
KMBEL	394832.93N/1041954.44W	Y	FB	TF	091.54	2.89			
BHIGH	394717.15N/1040845.34W	Y	FB	TF	098.29	8.69			
MMESA	394553.28N/1035543.50W	Y	FB	TF	097.85	10.14	AT/ABOVE 14000		
FALUJ	394524.52N/1035153.08W	Y	FB	TF	099.17	3.00			
EXTAN	394435.96N/1034526.05W	Y	FB	TF	099.20	5.04			
EXTAN	394435.96N/1034526.05W	Y	-	IF	-	-			
CABET	393538.96N/1020038.70W	Y	FB	TF	095.75	81.41			
SHAYK	393243.98N/1012434.30W	Y	FB	TF	095.77	28.05			



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED	EFFECTIVE DATE
EXTAN		SIX		EXTAN6.SHAYK		FIVE		07/11/2018	30 JAN 2020
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
CENTENNIAL (KAPA)									
RW17L (AER)	393502.91N/1045105.31W	N	-	-	-	-			CG 255 FT PER NM TO 8000
6400 MSL	-	-	-	VA	177.95	-			
	-	-	-	VM	177.95	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			
RW17R (AER)									
RW17R (AER)	393444.35N/1045113.39W	N	-	-	-	-			CG 370 FT PER NM TO 8000
6400 MSL	-	-	-	VA	177.95	-			
	-	-	-	VM	177.95	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			
RW35L (AER)									
RW35L (AER)	393335.23N/1045110.19W	N	-	-	-	-			
6400 MSL	-	-	-	VA	357.95	-			
	-	-	-	VM	357.95	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			
RW35R (AER)									
RW35R (AER)	393324.15N/1045100.74W	N	-	-	-	-			
6400 MSL	-	-	-	VA	357.95	-			
	-	-	-	VM	357.95	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)

DP NAME		NUMBER	DP COMPUTER CODE		SUPERSEDED NUMBER		DATED	EFFECTIVE DATE	
EXTAN		SIX	EXTAN6.SHAYK		FIVE		07/11/2018	30 JAN 2020	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
EXTAN	394435.96N/1034526.05W	Y	-	IF	-	-			
CABET	393538.96N/1020038.70W	Y	FB	TF	095.75	81.41			
SHAYK	393243.98N/1012434.30W	Y	FB	TF	095.77	28.05			
ROCKY MOUNTAIN METROPOLITAN		(KBJC)							
EXTAN	394435.96N/1034526.05W	Y	-	IF	-	-			
CABET	393538.96N/1020038.70W	Y	FB	TF	095.75	81.41			
SHAYK	393243.98N/1012434.30W	Y	FB	TF	095.77	28.05			
NORTHERN COLORADO RGNL		(KFNL)							
EXTAN	394435.96N/1034526.05W	Y	-	IF	-	-			
CABET	393538.96N/1020038.70W	Y	FB	TF	095.75	81.41			
SHAYK	393243.98N/1012434.30W	Y	FB	TF	095.77	28.05			
COLORADO AIR AND SPACE PORT		(KCFO)							
RW08 (AER)	394738.42N/1043354.88W	N	-	-	-	-			
6020 MSL	-	-	-	VA	091.15	-			
	-	-	-	VM	091.15	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			
RW17 (AER)	394708.14N/1043127.25W	N	-	-	-	-			
6020 MSL	-	-	-	VA	179.99	-			

QUALITY 9



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED	EFFECTIVE DATE
EXTAN		SIX		EXTAN6.SHAYK		FIVE		07/11/2018	30 JAN 2020
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
	-	-	-	VM	179.99	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			
RW26 (AER)	394736.82N/1043212.42W	N	-	-	-	-			
6020 MSL	-	-	-	VA	271.17	-			
	-	-	-	VM	271.17	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			
RW35 (AER)	394549.10N/1043127.23W	N	-	-	-	-			
6020 MSL	-	-	-	VA	359.99	-			
		-	-	VM	359.99	-			
EXTAN	394435.96N/1034526.05W	Y	FB	DF	-	-			
EXTAN	394435.96N/1034526.05W	Y	-	IF	-	-			
CABET	393538.96N/1020038.70W	Y	FB	TF	095.75	81.41			
SHAYK	393243.98N/1012434.30W	Y	FB	TF	095.77	28.05			

