

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION	RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33	Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	--	--

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW18 CLIMB TO 2100 DIRECT CISEV AND ON TRACK 142.44 TO HARCE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 081.65 INBOUND. CHART FAS OBST: 569 TREE 380158N/0885600W IXIPY TO RW18: 3.00/40. CHART MARION AWOS-3.
ENL VORTAC	JIMDA (FB)	147.33 / 12.12	3000	
ZOLLI	ZOBAM (FB)	177.77 / 3.90	3000	
JIMDA (IAF)	JODPU (NOPT) (FB)	136.23 / 5.00	2100	
ZOBAM (IAF)	JODPU (NOPT) (FB)	226.33 / 5.00	2100	
JODPU (IF/IAF)	IXIPY (FB)	181.28 / 6.10	2000	
IXIPY (FAF) (SEE FORM 8260-10)	UYADI/2.20 NM TO RW18 (FB)	181.28 / 2.57		

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.	HOLD N JODPU, RT, 181.28 INBOUND, 2100 FT. IN LIEU OF PT (IAF)				
3. FAC:	181.28	FAF:	IXIPY	DIST FAF TO MAP:	4.77 THLD: 4.77
4. MIN. ALT:	JODPU 2100, IXIPY 2000, UYADI/2.20 NM TO RW18 1180				
5. DIST TO THLD FROM OM:	MM:	IM:	150	HAT:	100 HAT: GS ANT:
6. MIN GS INCPT:	GS ALT AT:	OM:	MM:	IM:	
7. GS ANGLE:	TCH: 34:1 IS NOT CLEAR				
8. MSA FROM:	RW18 2700				

MAG VAR: 2W EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A	X					
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	860	1	420	860	1	420	860	1 1/8	420		NA				
CIRCLING	1000	1	556	1000	1	556	1000	1 1/2	556		NA				

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: USE MARION ALTIMETER SETTING; WHEN NOT RECEIVED, USE MOUNT VERNON ALTIMETER SETTING
 AND INCREASE ALL MDA 20 FEET AND INCREASE LNAV CAT C VISIBILITY TO 1 1/4 MILE.
 (SEE FORM 8260-10)



CITY AND STATE	ELEVATION: 444 THRE: 440	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
BENTON, IL	AIRPORT NAME:		RNAV (GPS) RWY 18, ORIG	AMDT: NONE
	BENTON MUNI		30 JUN 2011	DATED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
UYADI/2.20 NM TO RW18	RW18 (MAP) (FO)	181.28 / 2.20	
RW18 (MAP)	844 MSL	181.28	
844 MSL	CISEV (FB)		
CISEV	HARCE (FO)	142.44 / 13.30	2100

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ZOLLI ON V4 WESTBOUND AND V429 NORTHBOUND, AND ARRIVALS ON ENL VORTAC AIRWAY RADIALS 081 CW 225.

QUALITY
1
CHECKED

CITY AND STATE BENTON, IL	ELEVATION: 444	THRE: 440	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG 30 JUN 2011	SUP:
	AIRPORT NAME: BENTON MUNI				AMDT: NONE
					DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except MAF, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

QUALITY
A
CHECK

CITY AND STATE BENTON, IL	ELEVATION: 444 THRE: 440 AIRPORT NAME: BENTON MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG 30 JUN 2011	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
SEGMENT	12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012												
SUSAP H96 K5FR18	R	060HARCEK5EAOEY	010TF					1424	+ 02100			B JS	
SUSAP H96 K5FR18	R	070HARCEK5EAOEE	R HM					08170040	+ 02100			B JS	
RUNWAY	12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012												
SUSAP H96 K5GRW18	0040001813	N38005040W088560431+0100	+0104300440000040075R										
MSA	12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012												
SUSAP H96 K5SRW18	K5PG	0	18018002725									M	

QUALITY
A
CHECKED

CITY AND STATE

BENTON, IL

ELEVATION: 444

THRE: 440

AIRPORT NAME:

BENTON MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, ORIG

30 JUN 2011

SUP:

AMDT: NONE

DATED: