

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES												MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW09 CLIMB TO 2600 DIRECT HASUR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 273.83 INBOUND. CHART FAS OBST: 239 TREE 305900N/0844152W CHART FAS OBST: 197 TREE 305814N/0843844W CHART 192 TREE33 305826N/0843853W. DISTANCE TO THLD FROM 286 HAT: 0.77 NM. CHART VDP AT 1.13 MILES TO RW09* *LNAV ONLY. WAAS CHANNEL # 45915 REFERENCE PATH ID: W09A							
COLPA (IAF)		FILSI (NOPT) (FB)		003.58 / 5.00				2500									
HALUB (IAF)		FILSI (NOPT) (FB)		183.58 / 5.00				2500									
FILSI (IF/IAF)		JADSU (FB)		093.58 / 6.99				1800									
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD W FILSI, RT, 093.58 INBOUND, 2500 FT. IN LIEU OF PT (IAF) 3. FAC: <u>093.65</u> FAF: <u>JADSU</u> DIST FAF TO MAP: <u>5.01</u> THLD: <u>5.01</u> 4. MIN. ALT: <u>FILSI 2500, JADSU 1800</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>1800</u> GS ALT AT: <u>JADSU</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS NOT CLEAR 8. MSA FROM: <u> </u>												MAG VAR: 4W		EPOCH YEAR: 2010			
MINIMUMS																	
TAKEOFF: <u> </u>		☒ STANDARD		☒ SEE FAA FORM 8260-15A FOR THIS AIRPORT		ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	427	1	286	427	1	286	427	1	286	427	1	286					
LNAV/VNAV DA	467	1 1/4	326	467	1 1/4	326	467	1 1/4	326	467	1 1/4	326					
LNAV MDA	540	1	399	540	1	399	540	1	399	540	1 1/4	399					
CIRCLING	600	1	459	600	1	459	600	1 1/2	459	700	2	559					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: VDP AND BARO-VNAV NA WHEN USING TALLAHASSEE REGIONAL ALTIMETER SETTING. SEE 8260-10																	
CITY AND STATE BAINBRIDGE, GA				ELEVATION: 141 TDZE: 141 AIRPORT NAME: DECATUR CO INDUSTRIAL AIR PARK				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 11 FEB 2010				SUP: AMDT: ORIG-A DATED 06/04/2009			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TALLAHASSEE REGIONAL ALTIMETER SETTING AND INCREASE ALL DA 95 FEET AND ALL MDA 100 FEET; INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS AND LNAV CAT C/D VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	004/30 CW 184/30 (NOPT)	FILSI (IF/IAF) (FB)	2500
2.	184/30 CW 274/30	HALUB (IAF) (FB)	2500
3.	274/30 CW 004/30	COLPA (IAF) (FB)	2500

QUALITY
3
CHECKED

CITY AND STATE BAINBRIDGE, GA	ELEVATION: 141 TDZE: 141 AIRPORT NAME: DECATUR CO INDUSTRIAL AIR PARK	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 11 FEB 2010	SUP:
				AMDT: ORIG-A
				DATED: 06/04/2009

RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KBGE
RUNWAY RW09
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W09A
LTP/FTP LATITUDE 305822.1430N
LTP/FTP LONGITUDE 0843835.8810W
LTP/FTP ELLIPSOIDAL HEIGHT +00153
FPAP LATITUDE 305822.6000N
FPAP LONGITUDE 0843652.2400W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1072
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

692ADEA4

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K7
LTP ORTHOMETRIC HEIGHT +00431
FPAP ORTHOMETRIC HEIGHT +00431

CITY AND STATE

BAINBRIDGE, GA

ELEVATION: 141

TDZE: 141

AIRPORT NAME:

DECATUR CO INDUSTRIAL AIR PARK

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 9, AMDT 1

11 FEB 2010

SUP:

AMDT:

ORIG-A

DATED:

06/04/2009

QUALITY
3
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
OF LIFE

CITY AND STATE BAINBRIDGE, GA	ELEVATION: 141 TDZE: 141 AIRPORT NAME: DECATUR CO INDUSTRIAL AIR PARK	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 11 FEB 2010	SUP:
				AMDT: ORIG-A
				DATED: 06/04/2009