

**Federal Aviation
Administration**

Transmittal Letter 21-11

April 2, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/20/2021	MN	Fergus Falls	Fergus Falls Muni-Einar Mickelson Fld	1/4514	3/18/2021	VOR RWY 13, Amdt 1

AIRAC Date: 20 MAY 2021

FDC 1/4514 FFM IAP FERGUS FALLS MUNI-EINAR MICKELSON FLD, FERGUS FALLS, MN. VOR RWY 13, AMDT 1... S-13 CAT C/D VIS 1 3/8. CIRCLING CAT C MDA 1820/HAA 637, CAT D MDA 1940/HAA 757, CAT C VIS 1 3/4, CAT D VIS 2 1/2. EBABY FIX MINIMUMS: S-13 CAT C/D VIS 1 1/8. CIRCLING CAT C MDA 1820/HAA 637, CAT D MDA 1940/ HAA 757, CAT C VIS 1 3/4, CAT D VIS 2 1/2. DELETE NOTE: CAT D STRAIGHT-IN NA WHEN USING WHEATON ALTIMETER SETTING. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ELBOW LAKE ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET; INCREASE CIRCLING CAT C/D VISIBILITY 1/4 SM. EBABY FIX MINIMUMS INCREASE S-13 CAT C/D AND CIRCLING CAT C/D VISIBILITY 1/4 SM. THIS IS VOR RWY 13, AMDT 1A. 2103121442-PERM