

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW17 CLIMBING LEFT TURN TO 3000 DIRECT DEBKY AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 429 TREE 315029N/0940854W 559 AAO 315529N/0941138W. SIYGO TO RW17: 3.04/45. CHART NACOGDOCHES AWOS-3.											
CARTH (IAF)	DEBKY (NOPT) (FB)	183.53 / 6.39	3000												
DEBKY (IF/IAF)	SIYGO (FB)	166.51 / 6.01	2000												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N DEBKY, RT, 166.51 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 166.52 FAF: SIYGO DIST FAF TO MAP: 5.07 THLD: 5.07 4. MIN. ALT: DEBKY 3000, SIYGO 2000, SODVE/1.70 NM TO RW17 900 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW17 2200				MAG VAR: 4E EPOCH YEAR: 1995											
MINIMUMS															
TAKEOFF:	☐ STANDARD	☒ SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	☒											
CATEGORY =====>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	760	1	441	760	1	441	760	1 1/4	441						
CIRCLING	820	1	501	820	1	501	820	1 1/2	501		NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT CARTH VIA V13 NORTHBOUND. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. SEE 8260-10															
CITY AND STATE				ELEVATION: 319 TDZE: 319		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
CENTER, TX				AIRPORT NAME:		RNAV		RNAV (GPS) RWY 17, ORIG 29 JUL 2010				AMDT: NONE			
				CENTER MUNI								DATED			



**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: USE NACOGDOCHES ALTIMETER SETTING; WHEN NOT RECEIVED, USE HENDERSON ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.

CITY AND STATE

CENTER, TX

ELEVATION: 319 TDZE: 319

AIRPORT NAME:

CENTER MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 17, ORIG

29 JUL 2010

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
A
CHECKED

CITY AND STATE CENTER, TX	ELEVATION: 319 TDZE: 319 AIRPORT NAME: CENTER MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG 29 JUL 2010	SUP:	
				AMDT:	NONE
				DATED:	