

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
EMETT (IAF)	WUVOK (FB)	312.21 / 10.42	4400	LNAV: RW30
WUVOK (IF)	GACEP (FB)	300.97 / 6.10	4000	
				CLIMB TO 9000 DIRECT FOVAK AND VIA 295.13 TRACK TO HOVEL AND HOLD, CONTINUE CLIMB-IN-HOLD TO 9000.
				ADDITIONAL FLIGHT DATA: HOLD NW, RT, 145.42 INBOUND. CHART FAS OBST: 3019 TREE 440855N/1165116W GACEP TO RWY30: 3.05/50

- PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- PROFILE STARTS AT WUVOK
- FAC: 300.90 FAF: GACEP DIST FAF TO MAP: 5.66 THLD:
- MIN. ALT: WUVOK 4400, GACEP 4000
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS CLEAR
- MSA FROM: RW30 9000

MAG VAR: 15E

EPOCH YEAR: 2010

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: NA	X									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING	3480	1 1/4	1360	3480	1 1/2	1360	3480	3	1360	3480	3	1360			

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: PROCEDURE NA AT NIGHT.
CHART NOTE: USE ONTARIO ALTIMETER SETTING; WHEN NOT RECEIVED, USE BOISE ALTIMETER SETTING AND INCREASE ALL MDAS 160 FEET.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT EMETT VIA V4-444 SOUTHEAST BOUND

CITY AND STATE WEISER, ID	ELEVATION: 2120 TDZE: AIRPORT NAME: WEISER MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-A, ORIG	SUP: AMDT: NONE DATED
----------------------------------	---	------------------------------	--	-----------------------------

QUALITY
CHECKED

ALL AFFECTED PROCEDURES REVIEWED? ☒ YES ☐ NO		COORDINATES OF FACILITIES		REQUIRED EFFECTIVE DATE CONCURRENT	
COORDINATED WITH:					
ATA ☐	AAT ☐	ALPA ☐	APA ☐	AOPA ☒	NBAA ☒
				OTHER (specify) ☒	ZLC, BOI APPCON, ARPT MGR
FLIGHT CHECKED BY					
NAME: <i>Rick A. Webb</i> for Karl E. Wahlborg				AVN FIFO	DATE: 6-4-08
DEVELOPED BY					
NAME: <i>Grace Nowak</i> DEZ SILAGYI (GRACE NOWAK)				FIFO AVN-130	DATE: 04/28/2008
APPROVED BY					
NAME: <i>Rick A. Webb</i> RICK A. WEBB				FIFO AVN-130	DATE: JUN 10 2008
CHANGES:					
REASONS:					

EFFECTIVE CONCURRENT WITH AIRSPACE DOCKET #08-ANM-5

THIS IS AN UPDATED COPY OF THE FORM DEVELOPED ON 1/24/2008
 ADDED VERTICAL DESCENT ANGLE 3.05

QUALITY
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

PAGE 2 OF 3 PAGES

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	EMETT	EMETT	010	IAF	IF		FB				
	EMETT	WUVOK	020		TF		FB	1.0	312.2(327T)	010.4	04400
		WUVOK	010	FACF	IF		FB				04400
		GACEP	020	FAF	TF		FB	0.5	301.0(316T)	006.1	04000
		RW30	030	MAP	TF		FO	0.3	300.9(316T)	005.7	02170

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	FOVAK	040		DF		FB	1.0			
	HOVEL	050		TF		FO	1.0	295.1(310T)		09000
	HOVEL	060		HM	R	FO	2.0	145.4(160T)	007.0	09000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	EMETT	N435450.49	W1163807.41	N4354.842	W11638.124
	FOVAK	N441703.72	W1170406.08	N4417.062	W11704.101
	GACEP	N440758.93	W1165150.37	N4407.982	W11651.840
	HOVEL	N442132.65	W1171131.17	N4421.544	W11711.520
	WUVOK	N440335.82	W1164557.03	N4403.597	W11645.951
	RW30	N441202.61	W1165718.75	N4412.044	W11657.313

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH

CITY AND STATE
WEISER, ID

ELEVATION: 2120 TDZE:
AIRPORT NAME:
WEISER MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-A, ORIG

SUP:
AMDT: NONE
DATED:

QUALITY
CHECKED

[illegible]

NOTES / EXPLANATIONS FROM OPPOSITE SIDE OF FORM:
SEE ATTACHED AIRSPACE LETTER.

RW30: 4412.044N/11657.313W
EMETT: 4354.842N/11638.124W
WUVOK: 4403.597N/11645.951W
GACEP: 4407.982N/11651.840W
FOVAK: 4417.062N/11704.101W
HOVEL: 4421.545N-11711.521W

KS87: 2120 MSL
EDA: PRIMARY
3335 MSL 441549.70W-1165355.10W
2035 MSL 441145.00N-1165515.00W
SECONDARY:
3754 MSL 433633.00N-1160736.00W
2035 MSL 441145.00N-1165515.00W

TREE HEIGHT 100 FEET

2C ACCURACY CODE VERIFIED ON 1:24K MAP

VGSI DATA: 3.00/50

MINIMUMS NOT DEVELOPED PER FPO

PART B - SUPPLEMENTAL DATA											
1. COMMUNICATIONS WITH:			2. WEATHER SERVICE			3. ALTIMETER SETTING					
BOI APP CON BOI TOWER ZLC ARTCC			N W S		OTHER:		SOURCE:				
			F A A								
			A / C				DISTANCE:				
SATISFACTORY ON:			LOCATION:			HOURS REMOTE OPERATION:					
☒ V H F ☒ U H F ☐ H F			HRS OPTN:			ADJUSTMENT:					
4. MONITOR STATUS	PRIMARY					SECONDARY					
	NAVAID:					NAVAID:					
	MONITOR POINT:					MONITOR POINT:					
	HRS	CAT 1				HRS	CAT 1				
	OPTN:	CAT 3					OPTN:	CAT 3			
5. AIRSPACE		FLOOR OF CONTROLLED AIRSPACE UNDER FAC					CONTROL AREA				
		CONTROL ZONE:					HOURS OPTN			TRANSITION AREA	
6. APPROACH & RUNWAY LIGHTING	ALS					☒ REIL 12, 30 (PCL)					
	(S) SALS					TDZ					
	MALS					C/LINE					
	HIRL					☒ OTHER (SPECIFY) PAPI-4L 30					
	☒ MIRL 12, 30 (PCL)										
7. RUNWAY MARKINGS					8. RUNWAY VISUAL RANGE						
ALL WEATHER					APPROACH						
INSTRUMENT NPI-G 12, 30					ROLL OUT						
9. GLIDE SLOPE	G S ANGLE:					ELEV RWY THRESHOLD:					
	DISTANCE FROM RWY:					ELEV GS ANTENNA:					
						THRESHOLD CROSSING HEIGHT:					
10. FINAL APPROACH COURSE AIMING		☒	RUNWAY THRESHOLD			FT. FROM THRESHOLD					
		☒	ON CENTERLINE			FT. FROM CENTERLINE					
11. WAIVERS OF STANDARDS			NUMBER OF WAIVERS ON FILE NONE			DATES OF APPROVAL					
PART C - REMARKS: VDP NOT ESTABLISHED - CIRCLING ONLY. PRECIPITOUS TERRAIN EVALUATION COMPLETED. KONO ASOS IS ON SERVICE A KONO, DISTANCE 11.28 NM, 24 HR, 207.95 FT KBOI ASOS IS ON SERVICE A KBOI, DISTANCE 50.00 NM, 24 HR, 355.67 FT											
PART D - PREPARED BY: DEZ SILAGYI (GRACE NOWAK)						DATE: 01/24/2008					
TITLE: AERONAUTICAL INFORMATION SPECIALIST						OFFICE: AVN-130					

QUALITY
2
CHECKED