

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> 9A4	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 13	<u>ORIGINAL/AMENDMENT</u> 2D	<u>CITY</u> COURTLAND	<u>STATE</u> AL
<u>AIRPORT ELEVATION</u> 588	<u>TDZE</u> 582	<u>SUPERSEDED</u> RNAV (GPS) RWY 13	<u>ORIGINAL/AMENDMENT</u> 2C	<u>DATED</u> 11/27/2025
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 9 JULY 2026	<u>REQUIRED EFFECTIVE DATE</u> CONCURRENT WITH RNAV GPS RWY 31 2C.	<u>MAG VAR</u> 3W
				<u>EPOCH YEAR</u> 2015
				<u>CANCEL/SUSPEND</u>

TAA

THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 26-15.

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>ALTITUDE</u>
1. 043/30 CW 223/30	NOPT	GOCCI	IF/IAF	2700
2. 223/30 CW 043/30		223/10 CW 043/10		3200
3. 223/10 CW 043/10		GOCCI	IF/IAF	2700

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
GOCCI	IF/IAF	DAZNI		TF	FB	1.00	132.87	6.80	2000
DAZNI	FAF	RW13	MAP	TF	FO	0.30	132.93	4.33	
RW13	MAP	782 MSL		CA			132.93		
782 MSL		DABIE		DF	FO	1.00			2700

MISSED APPROACH

MAP:

LPV: DA
LNAV/VNAV: DA
LNAV: RW13

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 2700 DIRECT DABIE AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

QUALITY
10
CHECKED

PROFILE:

1.	PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)									
2.	HOLD NW GOCCI, RT, 132.87 INBOUND, 2700 IN LIEU OF PT (IAF), MAX 6000.														
3.	FAC:	132.93	FAF:	DAZNI	DIST FAF TO MAP:	4.33	DIST FAF TO THLD:	4.33							
4.	MIN ALT:	GOCCI 2700, DAZNI 2000													
5.	DIST TO THLD FROM OM:		MM:		IM:		150 HAT:		200 HAT:	0.50	GS ANT:				
6.	MIN GP INCPT:	2000	GP ALT AT PFAF:	DAZNI 2000					OM:		MM:			IM:	
7.	GP ANGLE:	3.00	34:1:	IS CLEAR	20:1:	IS CLEAR	TCH:	40.0							
8.	MSA FROM:														

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16°C OR ABOVE 54°C.

ADDITIONAL FLIGHT DATA:

HOLD SE, RT, 313.07 INBOUND.
FAS OBST: 762 AAO 344215N/0872348W.
CHART VDP AT 1.43 NM TO RW13.
WAAS CHANNEL # 56231
REFERENCE PATH ID: W13A
LTP HAE: 150.6 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LPV DA	782	3/4	200	782	3/4	200	782	3/4	200	782	3/4	200			
LNAV/VNAV DA	1075	1 3/8	493	1075	1 3/8	493	1075	1 3/8	493	1075	1 3/8	493			
LNAV MDA	1080	1	498	1080	1	498	1080	1 3/8	498	1080	1 3/8	498			
CIRCLING	1160	1	572	1240	1	652	1260	2	672	1360	2 1/2	772			

CHANGES - REASONS

- 1. REMOVED ALL CIRCLING ASSOCIATIONS TO RWY 18/36 - RUNWAY DEACTIVATED BY AIRPORT.
- 2. FPAP COORDINATES CHANGED FROM 343844.0600N/0871950.6500W TO 343844.0635N/0871950.6420W - CRC REMAINDER CHANGED FROM 25B6C00E TO 480B2F22 - NEW FAS DATA.
- 3. MINIMUMS: LPV VIS ALL CATS CHANGED FROM "3/4" TO "1" - IAW 8260.3G

06/02/26: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 05/05/26.

- 1. CHANGED LPV VIS ALL CATS FROM 1 TO 3/4.



COORDINATED WITH:

A4A

ALPA

AOPA

X

APA

HAI

NBAA

X

OTHER: ZME, AMGR, HSV APP CON

FLIGHT CHECKED BY

ADAM K STALVEY

Digitally signed by

ALLAN WILL

May 05, 2026

OFFICE

AJF

DATE

05/01/2026

DEVELOPED BY

ALLAN WILL (RODNEY SMITH)

Digitally signed by

ALLAN WILL

May 05, 2026

OFFICE

AJV-A4

DATE

01/09/2026

APPROVED BY

KYLE THOMPSON

Digitally signed by

ALLAN WILL

May 05, 2026

OFFICE

AJV-A4

DATE

TITLE
MANAGER

FAS DATA BLOCK INFORMATION

DATA FIELD
OPERATION TYPE
SBAS SERVICE PROVIDER IDENTIFIER
AIRPORT IDENTIFIER
RUNWAY
APPROACH PERFORMANCE DESIGNATOR
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR
REFERENCE PATH IDENTIFIER (APPROACH ID)
LTP/FTP LATITUDE
LTP/FTP LONGITUDE
LTP/FTP ELLIPSOIDAL HEIGHT
FPAP LATITUDE
FPAP LONGITUDE
THRESHOLD CROSSING HEIGHT (TCH)
TCH UNITS SELECTOR (METERS OR FEET USED)
GLIDEPATH ANGLE (GPA)
COURSE WIDTH AT THRESHOLD
LENGTH OFFSET
HORIZONTAL ALERT LIMIT (HAL)
VERTICAL ALERT LIMIT (VAL)

DATA
0
0
9A4
RW13
0
0
W13A
343941.4025N
0872113.4070W
+01506
343844.0635N
0871950.6420W
00040.0
F
03.00
106.75
1232
40.0
35.0

CRC REMAINDER

480B2F22

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE
LTP ORTHOMETRIC HEIGHT
FPAP ORTHOMETRIC HEIGHT

K7
+01772
+01772

