FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP) TITLE 14 CFR PART 97.37

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.

Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

AIRPORT ID KAUG STATE AMDT NO ACTUAL EFFECTIVE DATE

KAUG AUGUSTA ME 5 23 FEBRUARY 2023

TAKEOFF MINIMUMS:

RWY 35: STANDARD.

RWY 8: 300-1 1/8 OR STANDARD WITH MINIMUM CLIMB OF 272 FT PER NM TO 600.

RWY 17: 300-1 1/8 OR STANDARD WITH MINIMUM CLIMB OF 279 FT PER NM TO 600.

RWY 26: 400-1 7/8 OR STANDARD WITH MINIMUM CLIMB OF 315 FT PER NM TO 700.

TEXTUAL DEPARTURE PROCEDURES:

RWY 26: CLIMB ON HEADING 260.05 TO 800 BEFORE TURNING RIGHT.

RWY 35: CLIMB ON HEADING 351.10 TO 1000 BEFORE TURNING LEFT.

VISUAL CLIMB OVER AIRPORT:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 8: TREES, FENCE, POLE BEGINNING 25 FT FROM DER, 48 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/445 FT MSL.

TREES 117 FT FROM DER, 322 FT LEFT OF CENTERLINE, 100 FT AGL/442 FT MSL.

TREES BEGINNING 310 FT FROM DER, 15 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/445 FT MSL.

TOWER 5173 FT FROM DER, 1866 FT LEFT OF CENTERLINE, 156 FT AGL/527 FT MSL.

NOTE: RWY 17: TREES BEGINNING 42 FT FROM DER, 5 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/425 FT MSL.

TREES, POLES, VEHICLE ON ROAD, BUILDING BEGINNING 67 FT FROM DER, 51 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/442 FT MSL.

TREES 3860 FT FROM DER, 1460 FT RIGHT OF CENTERLINE, 100 FT AGL/448 FT MSL.

TREES BEGINNING 4131 FT FROM DER, 1598 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/481 FT MSL.

NOTE: RWY 26: POLE 30 FT FROM DER, 258 FT RIGHT OF CENTERLINE, 27 FT AGL/376 FT MSL.

POLE 34 FT FROM DER, 496 FT LEFT OF CENTERLINE, 30 FT AGL/379 FT MSL.

TREES BEGINNING 50 FT FROM DER, 22 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/442 FT MSL.

TREES BEGINNING 100 FT FROM DER, 15 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/442 FT MSL.

TREES BEGINNING 2161 FT FROM DER, 47 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/445 FT MSL.

TREES BEGINNING 5821 FT FROM DER, 784 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/501 FT MSL.

TOWER 5819 FT FROM DER, 962 FT RIGHT OF CENTERLINE, 186 FT AGL/573 FT MSL.

TOWER 1.4 NM FROM DER, 1488 FT RIGHT OF CENTERLINE, 180 FT AGL/665 FT MSL.

TOWER 1.5 NM FROM DER, 1401 FT RIGHT OF CENTERLINE, 199 FT AGL/658 FT MSL.

CONTROLLING OBSTACLES:

RWY 8: 527 FT MSL TOWER 441954.87N/0694629.52W.

RWY 17: 519 FT MSL TREE 441803.89N/0694733.64W.

RWY 26: 573 FT MSL TOWER 441844.00N/0694909.00W (CLIMB GRADIENT), 665 FT MSL TOWER 441835.00N/0694948.00W (CLIMB-TO ALTITUDE/CEILING), 658 FT MSL TOWER 441829.97N/0694958.65W (VISIBILITY).

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 26: 675 FT MSL TOWER 441848.26N/0695003.52W.

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 35: 847 FT MSL AAO 442200.00N/0695127.00W.

REMARKS:

100 FT VEGETATION USED PER FPT.

Digitally signed by

FLIGHT INSPECTED BY
JEREMY R VIRTSCASIMIR L TABAKAOFFICE
FPODATE
11/09/2022Nov 10, 202211/09/2022

DEVELOPED BYDigitally signed byOFFICEDATERICHARD CHRISTENSENRICHARD E CHRISTENSENAJV-A43109/16/2022

Oct 13, 2022

26 CHECKE

AIRPORT ID				CITY				STATE	AMDT NO	EFFECTIVE DATE	
KAU	IG				AUGUSTA				ME	5	23 FEBRUARY 2023
APPROVED BY					Digitally signed by		OFFI	CE	DATE		TITLE
JOHNNIE BAKER				ERIC N SUSKI		AJV-A	430			MANAGER	
					Oct 17, 202	2					
REQUIRED	EFFECTIV	E DATE:									
ROUTINE											
COORDINA	ATED WITH	:									
A4A 🗌	$\underline{ALPA} igmty$	AOPA 🔀	APA 🔀	HAI	NBAA 🔀	OTHER:	ZBW, PORTL	AND APP C	CON, AMGF	₹	
CHANGES	- REASON	<u>S</u> :									
I. UPDATE	D TAKEOF	F MINIMUN	IS RWY 8 FF	ROM "300-1 ⁻	1/8 OR STAND	ARD WITH	MINIMUM CL	IMB OF 273	FT PER N	M TO 600" 7	ΓΟ "300-1 1/8 OR
STANDARE	O WITH MIN	IIMUM CLIN	MB OF 272 F	T PER NM T	O 600" - NEW	OBSTACL	E EVALUATIO	N FOR UPD	DATED RW	Y DATA.	
2. UPDATE	D TAKEOF	F MINIMUM	1S RWY 17 F	ROM "300-1	1/8 OR STANI	DARD WIT	H MINIMUM C	LIMB OF 29	00 FT PER I	NM TO 600"	TO "300-1 1/8 OR
STANDARI	O WITH MIN	IIMUM CLIN	ИВ OF 279 F	T PER NM T	O 600" - NEW	OBSTACL	E EVALUATIO	N FOR UPD	DATED RW	Y DATA.	
3. UPDATE	D TAKEOF	F MINIMUM	1S RWY 26 F	ROM "400-1	7/8 OR STANI	DARD WIT	H MINIMUM C	LIMB OF 31	13 FT PER I	NM TO 800"	TO "400-1 7/8 OR
STANDARE	O WITH MIN	IIMUM CLIN	ИВ OF 315 F	T PER NM T	O 700" - NEW	OBSTACL	E EVALUATIO	N FOR UPD	DATED RW	Y DATA.	

- 4. UPDATED TAKEOFF OBSTACLE NOTES FOR ALL RWYS NEW OBSTACLE EVALUATION FOR UPDATED RWY DATA.
- 5. UPDATED CONTROLLING OBSTACLES FOR RWY 17 FROM 529 FT MSL TREE 441803.10N/0694733.04W TO 519 FT MSL TREE 441803.89N/0694733.64W NEW OBSTACLE EVALUATION AND MAP STUDY RESULTS.
- 6. OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 35 OBSTACLE CHANGED FROM 844 FT MSL AAO 442159.97N/0695127.24W TO 847 FT MSL AAO 442200.00N/0695127.00W NEW OBSTACLE EVALUATION RESULTS.
- 7. UPDATED CONTROLLING OBSTACLES RWY 26 VISIBILITY OBSTACLE COORDINATES FROM 441829.97N/0694858.65W TO 441829.97N/0694958.65W NEW OBSTACLE EVALUATION RESULTS.
- 8. UPDATED TEXTUAL DEPARTURE PROCEDURES RWY 26 HEADING FROM 260.04 TO 260.05 UPDATED RWY DATA.
- 9. ADDED REMARKS: 100 FT VEGETATION USED PER FPT FPT REQUEST.