

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 8.34 MILES AFTER TNP VORTAC OR AT TNP 8.34 DME FIX
JEHLI/TNP 10.00 DME (IF)	TNP VORTAC (NOPT)	255.35 / 10.00	4600	CLIMBING RIGHT TURN TO 5900 DIRECT TNP VORTAC AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5900.
				ADDITIONAL FLIGHT DATA: CHART FAS OBST: 2330 TREE 340637N/1155535W TNP VORTAC TO RW26: 3.13/40. CHART: SUNDANCE MOA. CHART AIRPORT ELEV: 1888

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD E TNP VORTAC, LT, 255.35 INBOUND, 4900 FT. IN LIEU OF PT (IAF)
3. FAC 264.22 FAF TNP VORTAC DIST FAF TO MAP 8.34 THLD 8.34
4. MIN. ALT TNP VORTAC 4600
8. MSA FROM: TNP VORTAC 285-145 5900, 145-285 7100

MAG VAR: 15E

EPOCH YEAR: 1965

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		X						
CATEGORY =====>		A			B			C			D			E				
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-26		3580	1 1/4	1745	3580	1 1/2	1745		NA			NA						
CIRCLING		3580	1 1/4	1692	3580	1 1/2	1692		NA			NA						

NOTES:

CHART NOTE: WHEN PALM SPRINGS INTL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA.
CHART NOTE: CIRCLING NA SOUTH OF RWY 8-26.
CHART NOTE: USE PALM SPRINGS INTL ALTIMETER SETTING.

CITY AND STATE TWENTYNINE PALMS, CA	ELEVATION: 1888 TDZE: 1835 AIRPORT NAME: TWENTYNINE PALMS	FACILITY IDENTIFIER: TNP	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 26, AMDT 2A 22 OCT 2009	SUP AMDT 2 DATE 03/12/2009
--	---	--------------------------------	--	----------------------------------