

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**

**TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> HAIGH FIELD	<u>AIRPORT ID</u> O37	<u>PROCEDURE NAME</u> RNAV (GPS) - A	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> ORLAND	<u>STATE</u> CA
<u>AIRPORT ELEVATION</u> 218	<u>TDZE</u>	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>MAG VAR</u> 14E
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 21 MAY 2020	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>	<u>EPOCH YEAR</u> 2020

**TERMINAL ROUTES**

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
SATNE		JEVLA		TF	FO	1.00	144.46	21.00	3000
TALUM	IAF	JEVLA	NOPT	TF	FB	1.00	336.64	14.12	3000
DURHA	IAF	JEVLA	NOPT	TF	FB	1.00	248.55	8.06	3000
JEVLA	IF/IAF	JILOX		TF	FB	1.00	279.94	6.00	2300
JILOX	FAF	MARBN	MAP	TF	FO	0.30	279.94	4.78	
MARBN	MAP	620 MSL		CA			279.94		
620 MSL		JITIM		DF	FO	1.00			4800

**MISSED APPROACH**

**MAP:**  
MARBN

**MISSED APPROACH INSTRUCTIONS:**

CLIMBING LEFT TURN TO 4800 DIRECT JITIM AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4800.

**ALTERNATE MISSED APPROACH INSTRUCTIONS:**



**PROFILE:**

1. PT      **SIDE OF COURSE**                      **OUTBOUND**                      **FT WITHIN**                      **MILES OF (IAF)**
2. HOLD E JEVLA, RT, 279.94 INBOUND, 3000 FT. IN LIEU OF PT (IAF), MAX 6000.
3. **FAC:** 279.94      **FAF:** JILOX                      **DIST FAF TO MAP:** 4.78                      **DIST FAF TO THLD:**
4. **MIN ALT:**    JEVLA 3000, JILOX 2300
5. **DIST TO THLD FROM OM:**                      **MM:**                      **IM:**                      **150 HAT:**                      **GS ANT:**
6. **MIN GP INCPT:**                      **GP ALT AT FAF :**                      **OM:**                      **MM:**                      **IM:**
7. **GP ANGLE:**                      **34:1:**                      **20:1:**                      **TCH:**
8. **MSA FROM:**    O37 7200

**PBN REQUIREMENTS NOTE:**

RNP APCH.

**NOTES:**

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT TALUM ON V23-195 SOUTHEAST BOUND.  
 CHART NOTE: USE CHICO ALTIMETER SETTING; WHEN NOT RECEIVED, USE REDDING ALTIMETER SETTING AND INCREASE ALL MDA 120 FEET. INCREASE VISIBILITY CAT C AND D 1/4 SM.

**ADDITIONAL FLIGHT DATA:**

FAC CROSSES MIDPOINT OF RWY 15-33.  
 CHART CIRCLING ICON.  
 FAS OBST: 370 AAO 394221N/1220424W.  
 HOLD N, RT, 167.30 INBOUND

**MINIMUMS:**

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

**ALTERNATE:** NA

CATEGORY:	A			B			C			D			E		
	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
CIRCLING	700	1	482	700	1	482	720	1 1/2	502	820	2	602			

**CHANGES - REASONS**

ORIGINAL PROCEDURE - PER ATC/FPT REQUEST (VOR MON).



**COORDINATED WITH:**

**A4A**  **ALPA**  **AOPA**  **APA**  **HAI**  **NBAA**  **OTHER:** ZOA, KO37 AMGR

*Digitally signed by*

**DONALD H LANIER**

Mar 17, 2020

*Digitally signed by*

**ROBERT GRIM**

Feb 13, 2020

*Digitally signed by*

**DONALD H LANIER**

Mar 17, 2020

**FLIGHT CHECKED BY**

JORDAN ROLIH

**OFFICE**

FICO

**DATE**

3/3/2020

**DEVELOPED BY**

ROBERT GRIM

**OFFICE**

AJV-A431

**DATE**

01/24/2020

**APPROVED BY**

GEORGE DAVIS

**OFFICE**

AJV-A430

**DATE**

**TITLE**  
MANAGER

