

**Federal Aviation
Administration**

Transmittal Letter 22-22

September 2, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/6/2022	IL	Kewanee	Kewanee Muni	2/5187	8/11/2022	RNAV (GPS) RWY 19, Amdt 1A

AIRAC Date: 6 OCTOBER 2022

FDC 2/5187 EZI IAP KEWANEE MUNI, KEWANEE, IL. RNAV (GPS) RWY 19, AMDT 1A... TAA STRAIGHT-IN 283/15 CW 103/15 TO YABYU MINIMUM ALTITUDE 2500. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. LPV VIS ALL CATS 1, LNAV/VNAV VISIBILITY ALL CATS 1 5/8. CHANGE ALTIMETER SETTING NOTE TO READ: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MOLINE ALTIMETER SETTING AND INCREASE LPV DA TO 1212 FEET; INCREASE LNAV/VNAV DA TO 1446 FEET AND ALL VISIBILITIES 1/8 SM. INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CAT C 1/8 SM, AND CIRCLING VISIBILITY CAT C 1/4. THIS IS RNAV (GPS) RWY 19, AMDT 1B. 2205171236-PERM