02/16/2021

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE

GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAME						NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
BNDIA						THREE	BNDIA3.BNDIA	TWO	12/07/2017	22 APR 2021
TYPE:	OBSTACLE	COPTER	SID	SPECIAL	RNAV					
			\boxtimes		\boxtimes					

DP ROUTE DESCRIPTION:

AUSTIN-BERGSTROM INTL

RWY 18L: CLIMB ON HEADING 174.70 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 18R: CLIMB ON HEADING 174.68 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 36L: CLIMB ON HEADING 354.69 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 36R: CLIMB ON HEADING 354.70 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE...

AUSTIN EXEC

RWY 13: CLIMB ON HEADING 126.43 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... **RWY 31:** CLIMB ON HEADING 306.43 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE...

SAN MARCOS RGNL

RWY 8: CLIMB ON HEADING 080.85 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 13: CLIMB ON HEADING 125.88 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 17: CLIMB ON HEADING 170.87 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 26: CLIMB ON HEADING 260.86 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 31: CLIMB ON HEADING 305.88 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 35: CLIMB ON HEADING 350.87 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE...

GEORGETOWN MUNI

RWY 11: CLIMB ON HEADING 114.56 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... **RWY 18:** CLIMB ON HEADING 177.54 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... **RWY 29:** CLIMB ON HEADING 294.56 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... **RWY 36:** CLIMB ON HEADING 357.54 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE...

LAGO VISTA TX - RUSTY ALLEN

RWY 15: CLIMB ON HEADING 157.29 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 33: CLIMB ON HEADING 337.29 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE...

TAYLOR MUNI

RWY 17: CLIMB ON HEADING 173.65 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... RWY 35: CLIMB ON HEADING 353.65 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE...

LAKEWAY AIRPARK

RWY 16: CLIMB ON HEADING 164.78 TO 1700, THEN AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE... **RWY 34:** CLIMB ON HEADING 344.77 OR AS ASSIGNED BY ATC FOR VECTORS TO CROSS GARDS AT OR ABOVE 5000, THENCE...

...ON TRACK 223.85 TO BNDIA. MAINTAIN ALTITUDE ASSIGNED BY ATC. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

OUALITL 5 CHECKE

NFDD N	No. 030			02/16/2021					27
DP NAME BNDIA			<u>NUMBER</u> THREE	DP COMPUTER CODE BNDIA3.BNDIA	SUPERSEDED NUMBER TWO		DATED 12/07/2017		ACTUAL EFFECTIVE DATE 22 APR 2021
TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):									
TRANSITION NAME	TRANSITION COMPUTER CODE	FROM FIX/NAVAID		<u>TO</u> NAVAID	COURSE	DISTANCE	<u>MEA</u>	MOCA	CROSSING ALTITUDE/FIXES

PROCEDURAL DATA NOTES:

NOTE: RADAR REQUIRED. NOTE: DME/DME/IRU OR GPS REQUIRED. NOTE: RNAV 1. NOTE (LAKEWAY AIRPARK ONLY): TAKEOFF RWY 16 REQUIRES A CLIMB TO 1700 ON HEADING 165 DEGREES PRIOR TO TURNING FOR OBSTACLE AVOIDANCE.

TAKEOFF MINIMUMS: AUSTIN-BERGSTROM INTL RWY 18L, 18R: STANDARD. RWY 36L, 36R: STANDARD WITH MINIMUM CLIMB OF 240 FT PER NM TO 2600.

AUSTIN EXEC RWY 16, 34: NA-ENVIRONMENTAL. RWY 13, 31: STANDARD.

SAN MARCOS RGNL RWY 8, 13, 17, 26: STANDARD. RWY 31: STANDARD WITH MINIMUM CLIMB OF 210 FT PER NM TO 2600. RWY 35: STANDARD WITH MINIMUM CLIMB OF 230 FT PER NM TO 2600.

GEORGETOWN MUNI RWY 11, 29, 36: STANDARD. RWY 18: 200-1 1/4 OR STANDARD WITH MINIMUM CLIMB OF 250 FT PER NM TO 1000.

LAGO VISTA TX - RUSTY ALLEN RWY 15, 33: STANDARD.

TAYLOR MUNI RWY 17, 35: STANDARD.

LAKEWAY AIRPARK RWY 34: STANDARD. RWY 16: 500-2 3/4 OR STANDARD WITH MINIMUM CLIMB OF 265 FT PER NM TO 1500.

TAKEOFF OBSTACLES NOTES: SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES: AUSTIN-BERGSTROM INTL RWY 36L, 36R: 2032 FT MSL TOWER 301836.00N/0974735.00W.

SAN MARCOS RGNL RWY 31, 35: 2049 FT MSL TOWER 300243.00N/0975251.00W.

GEORGETOWN MUNI RWY 18: 932 FT MSL ANTENNA ON BUILDING 303921.13N/0974101.53W.

CHECKE

LAKEWAY AIRPARK

RWY 16: 1326 FT MSL TOWER 301901.00N/0975922.00W. **OBSTACLE MANDATING ODP ROUTE DEVELOPMENT:** RWY 16: 1536 FT MSL TOWER 302026.00N/0980106.00W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KAUS 4E, EPOCH YEAR: 2020 DME/DME ASSESSMENT: SAT (RNP 2.0) CHART: TOP ALTITUDE: ASSIGNED BY ATC. CHART: MINIMUM CROSSING ALTITUDE AT GARDS - AT OR ABOVE 5000.

AIRPORTS SERVED:

AIRPORT NAME	AIRPORT ID	CITY	STATE
AUSTIN-BERGSTROM INTL	KAUS	AUSTIN	ТХ
AUSTIN EXEC	KEDC	AUSTIN	ТХ
SAN MARCOS RGNL	КНҮІ	AUSTIN	ТХ
GEORGETOWN MUNI	KGTU	GEORGETOWN	ТХ
LAGO VISTA TX - RUSTY ALLAN	KRYW	LAGO VISTA	ТХ
TAYLOR MUNI	KT74	TAYLOR	TX
LAKEWAY AIRPARK	K3R9	LAKEWAY	ТХ

COMMUNICATIONS:

AUSTIN-BERGSTOM INTL: ATIS, CLNC DEL, GND CON, TOWER, DEP CON, CPDLC. AUSTIN EXEC: AWOS, CLNC DEL, UNICOM, DEP CON. SAN MARCOS RGNL: AWOS, CLNC DEL, GND CON, TOWER, DEP CON. GEORGETOWN MUNI: ATIS, CLNC DEL, GND CON, TOWER, DEP CON, UNICOM. LAGO VISTA TX - RUSTY ALLEN: ASOS, UNICOM, DEP CON. TAYLOR MUNI: UNICOM, DEP CON. LAKEWAY AIRPARK: AWOS, UNICOM, DEP CON.

FIXES AND/OR NAVAIDS:

REMARKS:

1. ABBREVIATED AMENDMENT. FLIGHT INSPECTION MAPS AND RNAV PRO RUNS RETAINED FROM BNDIA TWO.

2. CLIMB GRADIENT USED TO MITIGATE KAUS RWY 36L/36R AND KHYI RWY 31/35 CONTROLLING OBSTACLES TO PERMIT UNRESTRICTED DEPARTURE HEADINGS PER ATC REQUEST. WALIT,

3. KAUS RWY 36L CLIMB GRADIENT ROUNDED TO 240 FT PER NM FOR PUBLICATION (COMPUTED VALUE 234 FT PER NM).

- 4. KAUS RWY 36R CLIMB GRADIENT ROUNDED TO 240 FT PER NM FOR PULICATION (COMPUTED VALUE 210 FT PER NM).
- 5. KHYI RWY 35 CLIMB GRADIENT ROUNDED TO 230 FT PER NM FOR PUBLICATION (COMPUTED VALUE 224 FT PER NM).

CHECKE

NFDD No. 030		02/16/2021			29
DP NAME BNDIA	NUMBER THREE	DP COMPUTER CODE BNDIA3.BNDIA	SUPERSEDED NUMBER TWO	<u>DATED</u> 12/07/2017	ACTUAL EFFECTIVE DATE 22 APR 2021
6. KHYI RWY 31 CLIMB GRADIENT ROUNDED TO 210 FT PER NM FOR PUBLIC FLIGHT INSPECTED BY PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJF-10) MEMO, APRIL 29, 2020 SUBJECT: FLIGHT INSPECTION REVIEW NOT	,	Digitally signed by ALLAN WILL Dec 22, 2020). OFFICE	DATE	
DEVELOPED BY Digitally signed by			OFFICE	DATE	
KELLIE BARNES KELLIE R BARNES			AJV-A423	11/13/2020	
Dec 07, 2020					
APPROVED BY			OFFICE	DATE	TITLE
MARLON ROBINSON		Digitally signed by ALLAN WILL	AJV-A420		MANAGER
REQUIRED EFFECTIVE DATE ROUTINE		Dec 22, 2020			

COORDINATED WITH:

CHANGES - REASONS:

1. CHANGED ALL KAUS RWY 17/35 REFERENCES TO RWY 18/36 - CURRENT AIRNAV DATA

2. REMOVED ALL TAKEOFF OBSTACLE NOTES AND ADDED "SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)." - 8260.46G

3. CHANGED DP ROUTE DESCRIPTIONS FROM "CLIMB HEADING" TO CLIMB ON HEADING" - 8260.46G

4. REMOVED "RADAR" FROM ALL DP ROUTE DESCRIPTIONS - WORDING PER 8260.46G APPENDIX E

5. CHANGED ALL REFERENCES TO AUSTIN EXECUTIVE TO AUSTIN EXEC - CURRENT AIRPORT NAME PER AIRNAV

OVALIT. 5 CHECKE

NFDD No. 030

02/16/2021

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE DEPARTURE (DATA RECORD)

DELARTORE (DATA RECORD)											
DP NAME						NUMBER	DP COMPUTER CODE	SUPERSE	EDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
BNDIA						THREE	BNDIA3.BNDIA		TWO	12/07/2017	22 APR 2021
FIX/NAVAID LAT/LONG		<u>C</u>	FO/FB	LEG TYPE	<u>TC</u>	<u>DIST</u> (NM)	ALTITUDE	<u>SPEED</u>		REMARKS	
GARDS	303007.52N/0975647.71W	Υ	-	IF	-	-	AT/ABOVE 5000				
BNDIA	293838.92N/0982740.22W	Y	FB	TF	227.85	36.29					