

**Federal Aviation
Administration**

Transmittal Letter 26-16

June 5, 2026

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/9/2026	NE	York	York Muni	6/4473	3/27/2026	RNAV (GPS) RWY 17, Amdt 2A

AIRAC Date: 9 JULY 2026

FDC 6/4473 JYR IAP YORK MUNI, YORK, NE. RNAV (GPS) RWY 17, AMDT 2A... LNAV/VNAV ALL CATS DA/HAT 2020/355. LNAV ALL CATS MDA/HAT 2020/355. CIRCLING CAT A MDA/HAA 2120/450. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE 3.00/TCH 40). DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT HELEK TO READ: HELEK/1.60 NM TO RW17 2220. CHANGE CHART VDP TO READ: CHART VDP AT 0.99 NM TO RW17. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUH ALTIMETER SETTING: INCREASE LPV DA TO 1973 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 2078 FEET; INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C 1/8 SM. CHANGE VDP AND BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING AUH ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -18C OR ABOVE 54C. CHANGE VISIBILITY REDUCTION BY HELICOPTERS NA NOTE TO READ: RWY 17 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 17, AMDT 2B. 2603261858-PERM