

**Federal Aviation  
Administration**

**Transmittal Letter 25-09**

**February 28, 2025**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/17/2025	VT	Rutland	Rutland/Southern Vermont Rgnl	5/5178	1/23/2025	RNAV (GPS) Z RWY 19, Amdt 1

**AIRAC Date: 17 APRIL 2025**

FDC 5/5178 RUT IAP RUTLAND/SOUTHERN VERMONT RGNL, RUTLAND, VT. RNAV (GPS) Z RWY 19, AMDT 1... DELETE NOTE: RNP APCH. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHART NOTE: VDP NA WHEN USING VSF ALTIMETER SETTING. CHART NOTE: FOR INOPERATIVE ALS WHILE USING VSF ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 1 3/8 MILES. DELETE PROFILE NOTE: \*LNAV ONLY. ALTERNATE MINIMUMS: CAT A, B, C 1800-5, NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE: \* FROM 2.95 NM TO RW19 VDP IN PROFILE VIEW. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY WHEN USING VSF ALTIMETER SETTING TO LNAV/VNAV ALL CATS AND LNAV CAT C. DELETE: \* FROM 2900 ALTITUDE AT CIBTO IN PROFILE VIEW. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VSF ALTIMETER SETTING AND INCREASE LPV DA TO 1281 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE LNAV/VNAV DA TO 2230 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/2 SM. THIS IS RNAV (GPS) Z RWY 19, AMDT 1A. 2501211312-PERM