

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW08 CLIMB TO 5700 DIRECT HOSOV AND ON TRACK 057.88 TO PETEZ AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5700. ADDITIONAL FLIGHT DATA: HOLD NE, LT, 237.88 INBOUND. CHART FAS OBST: 1552 TREE 462210N/1170133W DISTANCE TO THLD FROM 250 HAT: 0.64 NM. CHART VDP AT 1.09 NM TO RW08* *LNAV ONLY. WAAS CHANNEL # 97600 REFERENCE PATH ID: W08A LTP HAE: 416.7 M						
PIYOL		WESEV (TF) (FB) (RNP 2.00)			287.20 / 7.50			7200								
WESEV		EVOYU (TF) (FO) (RNP 2.00)			287.10 / 18.57			5000								
BIDDY (IAF)		EVOYU (NOPT) (TF) (FB) (RNP 1.00)			142.44 / 10.88			5000								
EVOYU (IF/IAF)		MABIZ (TF) (FB) (RNP 1.00)			083.58 / 3.72			4000								
MABIZ		GIYES (TF) (FB) (RNP 1.00)			083.65 / 2.23			3400								
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W EVOYU, LT, 083.58 INBOUND, 5000 FT. IN LIEU OF PT (IAF) 3. FAC: 083.69 FAF: GIYES DIST FAF TO MAP: 6.05 THLD: 6.05 4. MIN. ALT: EVOYU 5000, MABIZ 4000, GIYES 3400, WERAS/2.80 NM TO RW08 2360* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 3400 GS ALT AT: GIYES 3400 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS CLEAR 8. MSA FROM: RW08 7600																
										MAG VAR: 15E			EPOCH YEAR: 2010			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY ==>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	1690	3/4	250	1690	3/4	250	1690	3/4	250	1690	3/4	250				
LNAV/VNAV DA	1736	1	296	1736	1	296	1736	1	296	1736	1	296				
LNAV MDA	1820	1	380	1820	1	380	1820	1 1/8	380	1820	1 1/8	380				
CIRCLING	2000	1	558	2000	1	558	2000	1 1/2	558	2160	2 1/4	718				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -14C (7F) OR ABOVE 34C (93F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT PIYOL ON V253 SOUTHEAST BOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT BIDDY ON V536 NORTHEAST BOUND.																
CITY AND STATE LEWISTON, ID		ELEVATION: 1442 TDZE: 1440 AIRPORT NAME: LEWISTON-NEZ PERCE COUNTY			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 8, AMDT 2B 17 AUGUST 2017					SUP:				
												AMDT: 2A				
												DATED 06/26/2014				

QUALITY
 22
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
GIYES (FAF)	WERAS/2.80 NM TO RW08 (TF) (FB) (RNP 0.30)	083.69 / 3.25	
WERAS/2.80 NM TO RW08	RW08 (MAP) (TF) (FO) (RNP 0.30)	083.69 / 2.80	
RW08 (MAP)	1690 MSL (CA)	083.69	
1690 MSL	HOSOV (DF) (FB) (RNP 1.00)		
HOSOV	PETEZ (TF) (FO) (RNP 1.00)	057.88 / 14.65	5700

QUALITY
22
CHECKED

CITY AND STATE LEWISTON, ID	ELEVATION: 1442	TDZE: 1440	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 8, AMDT 2B 17 AUGUST 2017	SUP:
	AIRPORT NAME:				AMDT: 2A
	LEWISTON-NEZ PERCE COUNTY				DATED: 06/26/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KLWS
RUNWAY	RW08
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W08A
LTP/FTP LATITUDE	462225.5405N
LTP/FTP LONGITUDE	1170139.2815W
LTP/FTP ELLIPSOIDAL HEIGHT	+04167
FPAP LATITUDE	462211.9100N
FPAP LONGITUDE	1165932.1200W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0768
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

2F6A5D68

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K1
LTP ORTHOMETRIC HEIGHT	+04350
FPAP ORTHOMETRIC HEIGHT	+04350

QUALITY
22
CHECKED

CITY AND STATE

LEWISTON, ID

ELEVATION: 1442

TDZE: 1440

AIRPORT NAME:

LEWISTON-NEZ PERCE COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) Y RWY 8, AMDT 2B

17 AUGUST 2017

SUP:

AMDT:

2A

DATED:

06/26/2014