

**Federal Aviation
Administration**

Transmittal Letter 21-23

September 17, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/4/2021	IN	Bloomington	Monroe County	1/0243	9/2/2021	RNAV (GPS) RWY 35, Amdt 1A

AIRAC Date: 4 NOVEMBER 2021

FDC 1/0243 BMG IAP MONROE COUNTY, BLOOMINGTON, IN. RNAV (GPS) RWY 35, AMDT 1A... CIRCLING CAT D MDA 1620/HAA 774, VISIBILITY 2 1/2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TERRE HAUTE RGNL ALTIMETER SETTING; INCREASE LPV DA TO 1165, LNAV/VNAV DA TO 1465 AND ALL MDA 140 FEET AND INCREASE LPV ALL CATS, LNAV CAT C, D VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS AND CIRCLING C AND D VISIBILITY 1/2 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/2. THIS IS RNAV (GPS) RWY 35, AMDT 1B. 2109012010-PERM