

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE**  
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
SPI VORTAC	CAYAC/ 5.72 DME	036.00/5.72	2200	MAP: HEKOL / SPI 0.94 DME	
				CLIMB TO 2200 VIA SPI R-216 THEN RIGHT TURN DIRECT SPI VORTAC AND HOLD	
				ADDITIONAL FLIGHT DATA: HOLD SW, RT, 036.00 INBOUND CHART FAS OBST: 710 TANK 395344N/0893716W CHART VDP AT 1.90 DME; DISTANCE VDP TO THLD 0.97 MILES CAYAC TO RW22: 3.05/54 FAC CROSSES RWY C/L EXTENDED 4,220 FROM THLD CHART: ASR	

- PT L SIDE OF COURSE 036.00 OUTBOUND 2200 FT WITHIN 10 MILES OF CAYAC (IAF)
- 
- FAC 216.00 FAF CAYAC DIST FAF TO MAP - THLD 4.78
- MIN. ALT CAYAC 2200
- MSA FROM: SPI VORTAC 360-180 3100, 180-360 2700

MAG VAR: 1W EPOCH YEAR: 05

**MINIMUMS**

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A			STANDARD @					
CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-22	960	1/2	363	960	1/2	363	960	1/2	363	960	1	363			
CIRCLING	1020	1	423	1060	1	463	1060	1 1/2	463	1200	2	603			

NOTES: @ NA WHEN LOCAL WEATHER NOT AVAILABLE  
 CHART NOTES: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE LOGAN COUNTY ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET. VDP NA WHEN USING LOGAN COUNTY ALTIMETER SETTING.  
 FOR INOPERATIVE MALSR, INCREASE S-22 CAT D VISIBILITY TO 1 1/4.

CITY AND STATE  SPRINGFIELD, IL	ELEVATION: 597 TDZE: 597	FACILITY IDENTIFIER:  SPI	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:  OCT 27 2005 VOR/DME RWY 22, ORIG	SUP
	AIRPORT NAME:  ABRAHAM LINCOLN CAPITAL			AMDT NONE
				DATE