

**Federal Aviation
Administration**

Transmittal Letter 25-01

November 8, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/26/2024	TX	Hereford	Hereford Muni	4/1077	9/27/2024	RNAV (GPS) RWY 20, Orig-C

AIRAC Date: 26 DECEMBER 2024

FDC 4/1077 HRX IAP HEREFORD MUNI, HEREFORD, TX. RNAV (GPS) RWY 20, ORIG-C...
ADD NOTE: CIRCLING NA TO RWYS 14 AND 32. DELETE NOTE: BARO-VNAV NA WHEN
USING RICK HUSBAND AMARILLO INTL ALTIMETER SETTING. DELETE NOTE: VDP NA
WITH RICK HUSBAND AMARILLO INTL ALTIMETER SETTING. ADD NOTE: BARO-VNAV AND
VDP NA WHEN USING AMA ALTIMETER SETTING. CHANGE NOTE TO READ: FOR
UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -22 C OR ABOVE 41 C.
CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AMA
ALTIMETER SETTING: INCREASE LPV DA TO 4098 FEET AND ALL VISIBILITIES 1/4 SM;
INCREASE LNAV/VNAV DA TO 4232 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL
MDAS 120 FEET AND LNAV VISIBILITY CATS C AND D 1/2 SM, INCREASE CIRCLING
VISIBILITY CAT C 1/2 SM AND CAT D 1/4 SM. PBN REQUIREMENTS NOTE: RNP APCH -
GPS. DELETE PROFILE NOTE: *LNAV ONLY. DELETE ASTERISK FROM MINIMUM
ALTITUDE 4420 AT OLIVY 1.9 NM TO RW20. DELETE ASTERISK FROM VDP AT 1.2 NM TO
RW20. THIS IS RNAV (GPS) RWY 20, ORIG-D. 2409261915-PERM