

**Federal Aviation  
Administration**

**Transmittal Letter 16-09**

**March 11, 2016**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: .....EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
28-Apr-16	ME	Waterville	Waterville Robert Lafleur	5/0190	02/23/16	ILS OR LOC/DME RWY 5, Amdt 4A

**AIRAC Date: 28 APRIL 2016**

FDC 5/0190 WV L IAP WATERVILLE ROBERT LAFLEUR, WATERVILLE, ME. ILS OR LOC/DME RWY 5, AMDT 4A... S-LOC 5 MDA 680/HAT 371 ALL CATS. CHANGE VDP TO 2.19 DME\*, DISTANCE VDP TO THLD 1.13 NM, \*LOC ONLY. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUGUSTA ALTIMETER SETTING AND INCREASE S-ILS DA TO 544 AND ALL MDA 40 FEET. DELETE NOTE: FOR INOPERATIVE MALS F, INCREASE VISIBILITY S-ILS 5 ALL CATS TO 7/8 MILE, AND S-LOC 5 CAT D TO 1 MILE; WHEN USING AUGUSTA ALTIMETER INCREASE VISIBILITY S-LOC 5 CAT D TO 1 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUGUSTA ALTIMETER SETTING AND INCREASE S-ILS 5 DA TO 544; INCREASE ALL MDA 40 FEET AND S-LOC 5 CATS C/D VISIBILITY 1/4 MILE. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO S-ILS 5. FOR INOPERATIVE MALS F, INCREASE S-LOC 5 CAT D VISIBILITY TO 1 MILE. FOR INOPERATIVE MALS F, WHEN USING AUGUSTA ALTIMETER SETTING, INCREASE S-ILS 5 ALL CATS VISIBILITY TO 7/8 MILE AND S-LOC 5 CAT C/D VISIBILITY TO 1 1/8 MILE. THIS IS ILS OR LOC/DME RWY 5, AMDT 4B. 1512211857-PERM