

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
OLAKE	FOUR	OLAKE4.OLAKE	THREE	01/22/2026	9 JUL 2026

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	☐	☐	☒	☐	☒

DP ROUTE DESCRIPTION:

TAKEOFF RWY 10L: CLIMB ON HEADING 098.78 TO INTERCEPT COURSE 069.75 TO SMGLR, THEN ON TRACK 014.90 TO SONNC, THEN ON TRACK 295.01 TO CROSS AHABB AT OR ABOVE 6000, THEN ON TRACK 295.05 TO CROSS BAGGR AT OR ABOVE 10000, THENCE ...

TAKEOFF RWY 14: CLIMB ON HEADING 141.17 TO INTERCEPT COURSE 083.00 TO CRRMN, THEN ON TRACK 016.88 TO CROSS SMGLR, THEN ON TRACK 014.90 TO SONNC, THEN ON TRACK 295.01 TO CROSS AHABB AT OR ABOVE 6000, THEN ON TRACK 295.05 TO CROSS BAGGR AT OR ABOVE 10000, THENCE ...

TAKEOFF RWY 28R: CLIMB ON HEADING 278.79 TO 520, THEN DIRECT CRYER, CROSS CRYER AT OR ABOVE 2500, THEN ON TRACK 307.93 TO CROSS UTLEY AT OR ABOVE 4000, THEN ON TRACK 341.67 TO CROSS BAGGR AT OR ABOVE 10000, THENCE ...

TAKEOFF RWY 32: CLIMB ON HEADING 321.18 TO 520, THEN DIRECT BAYBE, THEN ON TRACK 319.00 TO CROSS BAGGR AT OR ABOVE 10000, THENCE ...

...ON TRACK 282.92 TO CROSS OLAKE AT OR ABOVE 11000, THEN ON TRANSITION. MAINTAIN 11000, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

ALL AIRCRAFT: CLIMB GRADIENTS: IF UNABLE TO ACCEPT CLIMB RATE ADVISE ATC PRIOR TO DEPARTURE. RUNWAYS 10L, 14, 28R, 32: 500 FT/NM TO 520.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
JAYMC	OLAKE4.JAYMC	OLAKE	JAYMC	278.56	31.85	FL180	1400	

PBN REQUIREMENT NOTES:

RNAV 1 - DME/DME/IRU OR GPS

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED.

PROCEDURAL DATA NOTES:

NOTE: JET AIRCRAFT ONLY

TAKEOFF MINIMUMS:

RWY 10L, 14, 28R, 32: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 520.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:**MSA:**

DJT, 2600



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
OLAKE	FOUR	OLAKE4.OLAKE	THREE	01/22/2026	9 JUL 2026

LOST COMMUNICATIONS PROCEDURES:**ADDITIONAL FLIGHT DATA:**

CHART: TOP ALTITUDE 11000.

AIRPORT MV: DJT 6W/2010.

DME/DME ASSESSMENT: SAT RNP 2.0.

CHART: MINIMUM CROSSING ALTITUDE AT BAGGR - AT OR ABOVE 10000.

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
DJT	WEST PALM BEACH	FL

COMMUNICATIONS:

CHART: ATIS, CLNC DEL. GND CON, TOWER, CPDLC

FIXES AND/OR NAVAIDS:**REMARKS:**

75 FOOT VEGETATION USED PER FPT.

WAIVER FOR NON STANDARD CLIMB GRADIENT TO BAGGR.

WAIVER FOR NON STANDARD CLIMB GRADIENT FOR LNAV ENGAGEMENT.

ABBREVIATED AMENDMENT

ORDER 8260.3G, LEGACY ICA USED FOR DESIGN AND EVALUATION

FLIGHT INSPECTED BY**SIGNATURE***Digitally signed by***OFFICE****DATE**Processed IAW Technical Support Group (AJF-17) Memo dated 07/07/2021, Guidance for Procedural Changes
Requiring Flight Inspection/Validation.**APRIL T SARMENTO**

Apr 21, 2026

DEVELOPED BY**SIGNATURE***Digitally signed by***JOHN F BRUNO**

Apr 20, 2026

OFFICE**DATE**

JOHN BRUNO

AJV-A432

04/09/2026

APPROVED BY**SIGNATURE***Digitally signed by***APRIL T SARMENTO**

Apr 21, 2026

OFFICE**DATE****TITLE**

CASIMIR TABAKA

AJV-A430

MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:**A4A** ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☒ **OTHER:** ZMA, PBI DEP CON, PBI ATCT, AMGR**CHANGES - REASONS:**

1. ALL INSTANCES OF PBI CHANGED TO DJT - IAW AP NAME CHANGE TO "PRESIDENT DONALD J TRUMP INTL"

2. REMARKS: REMOVED "THE ENVIRONMENTAL REVIEW UNDER ORDER 1050.1 (LATEST EDITION) AND THE NOISE SCREENING HAVE BEEN ACCOMPLISHED. (CARRY OVER)." - NOT REQUIRED

3. REMARKS: ADDED "ABBREVIATED AMENDMENT" AND "ORDER 8260.3G, LEGACY ICA USED FOR DESIGN AND EVALUATION" - IAW 8260.46K

QUALITY
42
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
OLAKE	FOUR	OLAKE4.OLAKE	THREE	01/22/2026	9 JUL 2026

<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW10L (AER)*	264058.97N/0800616.92W*	N	-	-	-	-			*DISPL THLD (1200 FT)
	264051.66N/0800329.65W	-	-	VI	092.78	2.50			CG 500 FT/NM TO 520
SMGLR	264303.25N/0795832.81W	Y	FB	CF	063.75	4.94			
SONNC	264724.82N/0795747.15W	Y	FB	TF	008.90	4.40			
AHABB	264832.70N/0800126.85W	Y	FB	TF	289.01	3.47	AT/ABOVE 6000		
BAGGR	265451.33N/0802154.79W	Y	FB	TF	289.05	19.35	AT/ABOVE 10000		
RW14 (AER)	264130.60N/0800614.48W	N	-	-	-	-			
	263936.61N/0800408.41W	-	-	VI	135.17	2.67			CG 500 FT/NM TO 520
CRRMN	264039.96N/0795903.47W	Y	FB	CF	077.00	4.67			
SMGLR	264303.25N/0795832.81W	Y	FB	TF	010.88	2.42			
SONNC	264724.82N/0795747.15W	Y	FB	TF	008.90	4.40			
AHABB	264832.70N/0800126.85W	Y	FB	TF	289.01	3.47	AT/ABOVE 6000		
BAGGR	265451.33N/0802154.79W	Y	FB	TF	289.05	19.35	AT/ABOVE 10000		
RW28R (AER)*	264055.13N/0800448.94W*	N	-	-	-	-			*DISPL THLD (811 FT)
520 MSL	-	-	-	VA	272.79	-	AT/ABOVE 520		CG 500 FT/NM TO 520
CRYER	264112.90N/0801215.10W	Y	FB	DF	-	-	AT/ABOVE 2500		
UTLEY	264322.89N/0801607.46W	Y	FB	TF	301.93	4.09	AT/ABOVE 4000		
BAGGR	265451.33N/0802154.79W	Y	FB	TF	335.67	12.56	AT/ABOVE 10000		

QUALITY
42
CHECKED

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
OLAKE		FOUR		OLAKE4.OLAKE		THREE		01/22/2026	9 JUL 2026
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW32 (AER)*	264044.85N/0800523.87W*	N	-	-	-	-			*DISPL THLD (418 FT)
520 MSL	-	-	-	VA	315.18	-	AT/ABOVE 520		CG 500 FT/NM TO 520
BAYBE	264507.52N/0801015.74W	Y	FB	DF	-	-			
BAGGR	265451.33N/0802154.79W	Y	FB	TF	313.00	14.24	AT/ABOVE 10000		
BAGGR	265451.33N/0802154.79W	Y	-	IF	-	-	AT/ABOVE 10000		
OLAKE	265729.75N/0804631.26W	Y	FB	TF	276.92	22.15	AT/ABOVE 11000		
OLAKE	265729.75N/0804631.26W	Y	-	IF	-	-	AT/ABOVE 11000		OLAKE4.JAYMC
JAYMC	265851.00N/0812208.00W	Y	FB	TF	272.56	31.85			

