

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE									
WAXUG (IAF)	TIDUY (FB)	085.20 / 5.00	2000	LPV: DA LNAV/VNAV: DA LNAV: RW36 CLIMB TO 2000 DIRECT AGAXE AND VIA 327.66 TRACK TO BIMTE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 147.66 INBOUND. DO NOT CHART. CHART FAS OBST: 204 POLE 294712N/0955349W CHART FAS OBST: 359 AAO 294433N/0955445W DISTANCE TO THLD FROM 250 HAT: 0.66 NM. CHART VDP AT 1.31 MILES TO RW36* *LNAV ONLY. WAAS CHANNEL # 97504 REFERENCE PATH ID: W36A								
CAROG (IAF)	TIDUY (FB)	265.30 / 5.00	2000									
TIDUY (IF)	ZATBA (FB)	355.25 / 6.00	2000									
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT TIDUY 3. FAC: <u>355.25</u> FAF: <u>ZATBA</u> DIST FAF TO MAP: <u>5.56</u> THLD: <u>5.56</u> 4. MIN. ALT: <u>TIDUY 2000, ZATBA 2000</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u>150</u> HAT: <u>100</u> HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>2000</u> GS ALT AT: <u>ZATBA</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS CLEAR 8. MSA FROM: <u>RW36 3100</u>				MAG VAR: 4E EPOCH YEAR: 2010								
MINIMUMS												
TAKEOFF: ☐ STANDARD ☒ SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A ☒												
CATEGORY =====>	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	414	1	250	414	1	250	414	1	250	414	1	250
LNAV/VNAV DA	662	1 3/4	498	662	1 3/4	498	662	1 3/4	498	662	1 3/4	498
LNAV MDA	620	1	456	620	1	456	620	1 1/4	456	620	1 1/2	456
CIRCLING	820	1	654	820	1	654	820	1 3/4	654	880	2 1/4	694
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING DAVID WAYNE HOOKS MEMORIAL ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: RADAR REQUIRED SEE 8260-10												
CITY AND STATE		ELEVATION: 166 TDZE: 164		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP:				
HOUSTON, TX		AIRPORT NAME: HOUSTON EXECUTIVE				RNAV (GPS) RWY 36, AMDT 1 07 MAY 2009		AMDT: ORIG				
								DATED 08/30/2007				

TL09-09 PUB 5-7-09

CHECKED