

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM	TO	COURSE AND DISTANCE	ALTITUDE														
SOXCO (IAF)	ARUYY (NOPT) (FB)	210.79 / 5.00	1900	LPV: DA LNAV/VNAV: DA LNAV: RW12 CLIMB TO 2000 DIRECT MIEGE AND RIGHT TURN VIA TRACK 210.95 TO HOLBI AND VIA TRACK 288.60 TO ODAZO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 063.79 INBOUND. CHART FAS OBST: 209 TREE 310243N/0870438W CHART FAS OBST: 479 TOWER 310355N/0870900W DISTANCE TO THLD FROM 250 HAT: 0.67 NM. CHART VDP AT 1.61 MILES TO RW12* *LNAV ONLY. WAAS CHANNEL # 53416 REFERENCE PATH ID: W12A													
REVBE (IAF)	ARUYY (NOPT) (FB)	030.75 / 5.00	1900														
ARUYY (IF/IAF)	EHEBA (FB)	120.77 / 6.22	1900														
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NW ARUYY, RT, 120.77 INBOUND, 1900 FT. IN LIEU OF PT (IAF) 3. FAC: <u>120.82</u> FAF: <u>EHEBA</u> DIST FAF TO MAP: <u>5.48</u> THLD: <u>5.48</u> 4. MIN. ALT: <u>ARUYY 1900, EHEBA 1900</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>1900</u> GS ALT AT: <u>EHEBA</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>45.5</u> 34:1 IS CLEAR 8. MSA FROM: <u> </u>										MAG VAR: 1W		EPOCH YEAR: 2000					
MINIMUMS																	
TAKEOFF: <u> </u>		☒ STANDARD		☒ SEE FAA FORM 8260-15A FOR THIS AIRPORT		ALTERNATE: N A		☒									
CATEGORY =====>	A			B			C			D			E				
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	341	1	250	341	1	250	341	1	250	341	1	250					
LNAV/VNAV DA	479	1 1/2	388	479	1 1/2	388	479	1 1/2	388	479	1 1/2	388					
LNAV MDA	640	1	549	640	1	549	640	1 1/2	549	640	1 3/4	549					
CIRCLING	660	1	561	660	1	561	660	1 1/2	561	700	2	601					
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING PENSACOLA ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PENSACOLA ALTIMETER SETTING AND SEE 8260-10																	
CITY AND STATE				ELEVATION: 99 TDZE: 91				FACILITY IDENTIFIER:				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:	
BREWTON, AL				AIRPORT NAME:				RNAV				RNAV (GPS) RWY 12, ORIG 11 MAR 2010				AMDT: NONE	
				BREWTON MUNI												DATED	

QUALITY
6
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

INCREASE ALL DA 84 FEET AND ALL MDA 100 FEET; INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS, LNAV AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE.

CHART NOTE: VDP NA WHEN USING PENSACOLA ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	031/30 CW 211/30 (NOPT)	031/7 CW 211/7	2000
	031/7 CW 211/7	ARUYY (IF/IAF) (FB)	1900
2.	211/30 CW 301/30	SOXCO (IAF) (FB)	2300
3.	301/30 CW 031/30	REVBE (IAF) (FB)	3000

QUALITY
6
CHECKED

CITY AND STATE

BREWTON, AL

ELEVATION: 99

TDZE: 91

AIRPORT NAME:

BREWTON MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

RNAV (GPS) RWY 12, ORIG

11 MAR 2010

SUP:

AMDT: NONE

DATED:

**RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	12J
RUNWAY	RW12
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W12A
LTP/FTP LATITUDE	310305.7155N
LTP/FTP LONGITUDE	0870422.5820W
LTP/FTP ELLIPSOIDAL HEIGHT	-00027
FPAP LATITUDE	310221.2400N
FPAP LONGITUDE	0870252.6500W
THRESHOLD CROSSING HEIGHT (TCH)	00045.5
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

844BB00B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00250
FPAP ORTHOMETRIC HEIGHT	+00250

QUALITY
9
CHECKED

CITY AND STATE

BREWTON, AL

ELEVATION: 99 TDZE: 91

AIRPORT NAME:

BREWTON MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

RNAV (GPS) RWY 12, ORIG

11 MAR 2010

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 12J K7FR12	AARUY	010ARUYK7EA0EE	AR	HF			12080040	+ 01900		18000		A JS	
SUSAP 12J K7FR12	AREVBE	010REVBK7EA0E	A	IF						18000		A JS	
SUSAP 12J K7FR12	AREVBE	020ARUYK7EA0EE	B	010TF			03080050	+ 01900				A JS	
SUSAP 12J K7FR12	ASOXCO	010SOXCOK7EA0E	A	IF						18000		A JS	
SUSAP 12J K7FR12	ASOXCO	020ARUYK7EA0EE	B	010TF			21080050	+ 01900				A JS	
SUSAP 12J K7FR12	R	010ARUYK7EA0E	I	IF				+ 01900		18000		A JS	
SUSAP 12J K7FR12	R	020EHEBAK7EA1E	F	051TF			12080062	+ 01900				A JS	
SUSAP 12J K7FR12	R	020EHEBAK7EA2WALPV			ALNAV/VNAV	ALNAV						JS	
SUSAP 12J K7FR12	R	030RW12 K7PGOGY M	031TF				12080055		00127	-300		A JS	
SUSAP 12J K7FR12	R	040	0 M	010CA			1208	+ 00341				A JS	
SUSAP 12J K7FR12	R	050MIECEK7EA0E		010DF								A JS	
SUSAP 12J K7FR12	R	060HOLBIK7EA0E		R010TFY			2110					A JS	
SUSAP 12J K7FR12	R	0700DAZOK7EA0EY		C10TF			2886	+ 02000				A JS	
SUSAP 12J K7FR12	R	0800DAZOK7EA0EE		R020HM			06380040	+ 02000				A JS	

[illegible]

QUALITY
6
CHECKED

CITY AND STATE BREWTON, AL	ELEVATION: 99 TDZE: 91 AIRPORT NAME: BREWTON MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 11 MAR 2010	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
PP	12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012												
SUSAP 12J K7PR12	RW12 001 0000W12A0N3103057155W08704225820-000270300N3102212400W08702526500106751224000455P400500844BB00B												
SUSAP 12J K7PR12	RW12 002E +00250+00250LPV 53416												



CITY AND STATE BREWTON, AL	ELEVATION: 99 TDZE: 91	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 11 MAR 2010	SUP:
	AIRPORT NAME: BREWTON MUNI			AMDT: NONE
				DATED: