

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SCUBY	EIGHT	SCUBY8.SCUBY	SEVEN	04/27/2017	<b>5 Sep 2024</b>

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**DP ROUTE DESCRIPTION:**

TAKEOFF RWY 6: CLIMBING RIGHT TURN HEADING 100 OR AS ASSIGNED FOR VECTORS TO JOIN FILED ROUTE, THENCE...  
 TAKEOFF RWY 24: CLIMBING LEFT TURN HEADING 220 OR AS ASSIGNED FOR VECTORS TO JOIN FILED ROUTE, THENCE...  
 ...ALL AIRCRAFT MAINTAIN 3000 OR ASSIGNED ALTITUDE. EXPECT FURTHER CLEARANCE TO FILED ALTITUDE WITHIN 10 MINUTES AFTER DEPARTURE.

**TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):**

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	---------------------------------	------------------------	----------------------	---------------	-----------------	------------	-------------	--------------------------------

**PBN REQUIREMENT NOTES:**

**EQUIPMENT REQUIREMENT NOTES:**

RADAR REQUIRED

**PROCEDURAL DATA NOTES:**

**TAKEOFF MINIMUMS:**

RWY 6, 24: STANDARD

**TAKEOFF OBSTACLES NOTES:**

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

**CONTROLLING OBSTACLES:**

**MSA:**

FROM RSW VORTAC, 2600.

**LOST COMMUNICATIONS PROCEDURES:**

**ADDITIONAL FLIGHT DATA:**

CHART: TOP ALTITUDE: 3000  
 AIRPORT MV: RSW 4W/2000

**AIRPORTS SERVED:**

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
KRSW	FORT MYERS	FL



<b>DP NAME</b> SCUBY	<b>NUMBER</b> EIGHT	<b>DP COMPUTER CODE</b> SCUBY8.SCUBY	<b>SUPERSEDED NUMBER</b> SEVEN	<b>DATED</b> 04/27/2017	<b>ACTUAL EFFECTIVE DATE</b> <b>5 Sep 2024</b>
-------------------------	------------------------	---	-----------------------------------	----------------------------	---

**COMMUNICATIONS:**

CHART: ARTCC, ATIS, CLNC DEL, CTAF, GND CON, TWR.

**FIXES AND/OR NAVAIDS:**

PIE VORTAC, ORL VORTAC, LAL VORTAC, SRQ VOR/DME, RSW VORTAC, EYW VORTAC.

**REMARKS:**

ABBREVIATED AMENDMENT.  
DEPARTURE PROCEDURE TRAPEZOID BUILT TO 1500 FT MSL (MINIMUM VECTOR ALTITUDE).

**FLIGHT INSPECTED BY**

**SIGNATURE**

**OFFICE**

**DATE**

*Digitally signed by*

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 SUBJECT: GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

**ALLAN WILL**

Feb 23, 2024

**DEVELOPED BY**

**SIGNATURE**

**OFFICE**

**DATE**

ALLAN WILL (HENRY BRADSHAW)

*Digitally signed by*

**ALLAN WILL**

AJV-A423

09/05/2024

Feb 23, 2024

**APPROVED BY**

**SIGNATURE**

**OFFICE**

**DATE**

**TITLE**

ALLAN WILL

*Digitally signed by*

**ALLAN WILL**

AJV-A423

MANAGER

**REQUIRED EFFECTIVE DATE**

Feb 23, 2024

ROUTINE

**COORDINATED WITH:**

**A4A**  **ALPA**  **AOPA**  **APA**  **HAI**  **NBAA**  **OTHER:**ZMA, RSW DEP CON, AMGR

**CHANGES - REASONS:**

1. TAKEOFF OBSTACLE NOTES: DELETED RWY 6/24 TAKEOFF OBSTACLE NOTES AND ADDED "SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)" - 8260.46J, APP. E, SEC. 1, 2.I.
2. COMMUNICATIONS: REMOVED "DEP CON 119.75 327.8" - 8260.46J, SEC. 2, 2O.
3. FIXES AND/OR NAVAIDS: REMOVED "LBV VORTAC, CYY VOR/DME, AND PHK VOR/DME" - LBV, PHK, AND CYY VORMON.
4. REMARKS: REMOVED "SCUBY SEVEN AMENDMENT DOES NOT SATISFY PERIODIC REVIEW REQUIREMENTS." - NO LONGER REQUIRED.
5. DP ROUTE DESCRIPTION: UPDATED "TAKE-OFF" TO "TAKEOFF", AND CHANGED "RYW 24" TO "RWY 24" - FORMAT AND SPELLING.
6. EQUIPMENT REQUIREMENT NOTES: ADDED "RADAR REQUIRED" - 8260.46J, APP. D, SECTION 2.2.F.(3)
7. TAKEOFF MINIMUMS: CHANGED "RWY 6, 24 STANDARD" TO "RWY 6, 24: STANDARD" - 8260.46J, APP. D, SEC. 2. H.
8. MSA: ADDED "FROM RSW VORTAC, 2600." - 8260.46J, APP. D, SEC. 2. K.
9. ADDITIONAL FLIGHT DATA: ADDED "AIRPORT MV: RSW 4W/2000" - IFP MEMO 283
10. REMARKS: ADDED "ABBREVIATED AMENDMENT" - 8260.46J, APP. D, SEC. 2, 2.Q.(3).

