

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
MARIC	HOTIL (FO)	349.46 / 21.07	3400	LPV: DA LNAV/VNAV: DA LNAV: RW12L	
EHF VORTAC	HOTIL (FO)	297.05 / 9.50	3400	CLIMB TO 3000 DIRECT ULEYE AND RIGHT TURN ON TRACK 222.95 TO MARIC AND HOLD.	
COREZ (IAF)	HOTIL (NOPT) (FB)	066.68 / 11.91	3400		
PONDD (IAF)	HOTIL (NOPT) (FB)	161.11 / 14.15	3400	ADDITIONAL FLIGHT DATA: HOLD NE, RT, 221.00 INBOUND. CHART FAS OBST: 650 TOWER 352727N/1190457W CHART FAS OBST: 668 TRMSN TWR 352727N/1190428W DISTANCE TO THLD FROM 250 HAT: 0.62 NM. WAAS CHANNEL # 78418 REFERENCE PATH ID: W12A LTP HAE: 122.1 M	
HOTIL (IF/IAF)	JIBOP (FB)	121.21 / 6.01	2500		
JIBOP (FAF)	HOVGA/2.80 NM TO RW12L	121.25 / 3.19			
HOVGA/2.80 NM TO RW12L (SEE FORM 8260-10)	RW12L (MAP) (FO)	121.30 / 2.80			

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD NW HOTIL, RT, 121.21 INBOUND, 3400 FT. IN LIEU OF PT (IAF)
- FAC: 121.26 FAF: JIBOP DIST FAF TO MAP: 5.99 THLD: 5.99
- MIN. ALT: HOTIL 3400, JIBOP 2500, HOVGA/2.80 NM TO RW12L 1440\*
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT: 2500 GS ALT AT: JIBOP 2500 OM:        MM:        IM:
- GS ANGLE: 3.00 TCH: 52.0 34:1 IS NOT CLEAR
- MSA FROM: RW12L 8800

MAG VAR: 14E EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
	A		B		C		D		E						
CATEGORY	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	760	1	250	760	1	250	760	1	250	760	1	250			
LNAV/VNAV DA	1073	2	563	1073	2	563	1073	2	563	1073	2	563			
LNAV MDA	920	1	410	920	1	410	920	1 1/4	410	920	1 1/4	410			
CIRCLING	940	1	430	960	1	450	960	1 1/2	450	1060	2	550			

NOTES:  
 CHART NOTE: CIRCLING NA NE OF RWY 12L/30R.  
 CHART NOTE: BARO-VNAV NA WHEN USING PORTERVILLE ALTIMETER SETTING.  
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 48C (118F).  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 (SEE FORM 8260-10)

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY  
5  
CHECKED

CITY AND STATE BAKERSFIELD, CA	ELEVATION: 510 TDZE: 510	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12L, AMDT 1A 21 OCT 2010	SUP:
	AIRPORT NAME: MEADOWS FIELD			AMDT: 1
				DATED 07/29/2010

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW12L (MAP)	760 MSL	121.30	
760 MSL	ULEYE (FB)		
ULEYE	MARIC (FO)	222.95 / 16.05	3000

NOTES, (CONT.):

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

\*LNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PORTERVILLE ALTIMETER SETTING AND INCREASE ALL DA 92 FEET, ALL MDA 100 FEET, INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS AND LNAV CATS C/D VISIBILITY 1/4 MILE.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT EHF VORTAC ON V165 SOUTHBOUND.



CITY AND STATE BAKERSFIELD, CA	ELEVATION: 510	TDZE: 510	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12L, AMDT 1A	SUP:
	AIRPORT NAME: MEADOWS FIELD			21 OCT 2010	AMDT: 1
					DATED: 07/29/2010

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBFL
RUNWAY	RW12L
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W12A
LTP/FTP LATITUDE	352646.8190N
LTP/FTP LONGITUDE	1190416.5750W
LTP/FTP ELLIPSOIDAL HEIGHT	+01221
FPAP LATITUDE	352530.4900N
FPAP LONGITUDE	1190244.3400W
THRESHOLD CROSSING HEIGHT (TCH)	00052.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0000
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER 4D594742

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+01553
FPAP ORTHOMETRIC HEIGHT	+01553



CITY AND STATE BAKERSFIELD, CA	ELEVATION: 510	TDZE: 510	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12L, AMDT 1A 21 OCT 2010	SUP:
	AIRPORT NAME: MEADOWS FIELD				AMDT: 1
					DATED: 07/29/2010



