

**Federal Aviation
Administration**

Transmittal Letter 22-23

September 16, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/3/2022	PA	Pittsburgh	Allegheny County	2/4945	9/9/2022	RNAV (GPS) RWY 28, Amdt 3A

AIRAC Date: 3 NOVEMBER 2022

FDC 2/4945 AGC IAP ALLEGHENY COUNTY, PITTSBURGH, PA. RNAV (GPS) RWY 28, AMDT 3A... CHART NOTE: CIRCLING RWY 13 NA AT NIGHT. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. DELETE NOTE: CHART VDP AT 1.25 NM TO RW28*. CHART VDP 1.23 NM TO RW28. ALTERNATE MINIMUMS: STANDARD - EXCEPT CAT D 800-2 1/4. LNAV/VNAV VISIBILITY ALL CATS RVR 3500. LNAV VISIBILITY CATS C/D RVR 4500. CHANGE CHART FAS OBST: 1353 TREE (42-062755) 402121N/0795415W. CHANGE INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LPV ALL CATS VISIBILITY TO RVR 4500 AND LNAV/VNAV ALL CATS VISIBILITY TO RVR 5500. MISSED APPROACH: CLIMB TO 3000 DIRECT MESIE AND ON COURSE 197.13 TO AGC VOR/DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000. THIS IS RNAV (GPS) RWY 28, AMDT 3B. 2208051515-PERM