

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE									
COOLI	EMUME (FO)	043.30 / 31.88	10900	LPV: DA LNAV/VNAV: DA LNAV: RW23 CLIMB TO 12000 DIRECT SOLNE AND VIA 212.13 TRACK TO COOLI AND HOLD, CONTINUE CLIMB-IN-HOLD TO 12000. ADDITIONAL FLIGHT DATA: HOLD S, LT, 352.88 INBOUND. CHART FAS OBST: 7143 RW23 411643N/1110121W CHART FAS OBST: 7215 POLE 411628N/1110132W CHART 8479 TREE 412101N/1105449W. DISTANCE TO THLD FROM 250 HAT: 0.66 NM. CHART VDP AT 1.06 MILES TO RW23* *LNAV ONLY. WAAS CHANNEL # 77905 REFERENCE PATH ID: W23A								
PACKY	EMUME (FO)	067.12 / 25.84	10900									
FBR VOR/DME (IAF)	EMUME (NOPT) (FB)	256.07 / 13.61	9900									
EMUME (IF/IAF)	CESLA (FB)	233.97 / 8.68	9100									
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NE EMUME, RT, 233.97 INBOUND, 9900 FT. IN LIEU OF PT (IAF) 3. FAC: 233.85 FAF: CESLA DIST FAF TO MAP: 5.92 THLD: 5.92 4. MIN. ALT: EMUME 9900, CESLA 9100, JADUR/1.70 NM TO RW23 7700* 5. DIST TO THLD FROM OM: MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: 9100 GS ALT AT: CESLA OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: 3.00 TCH: 46.8 34:1 IS CLEAR 8. MSA FROM: RW23 12400				MAG VAR: 13E EPOCH YEAR: 2005								
MINIMUMS												
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD							
CATEGORY =====>	A		B		C		D		E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	7393	1/2	250	7393	1/2	250	7393	1/2	250	7393	1/2	250
LNAV/VNAV DA	7443	1/2	300	7443	1/2	300	7443	1/2	300	7443	3/4	300
LNAV MDA	7520	1/2	377	7520	1/2	377	7520	1/2	377	7520	1	377
CIRCLING	7580	1	437	7720	1	577	7760	1 3/4	617	7760	2	617
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -29C (-20F) OR ABOVE 34C (93F). CHART NOTE: DME/DME RNP-0.3 NA. SEE 8260-10												
CITY AND STATE			ELEVATION: 7143 TDZE: 7143		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:		
EVANSTON, WY			AIRPORT NAME:		RNAV		RNAV (GPS) RWY 23, AMDT 4 JAN 17 2008			AMDT: 3		
			EVANSTON-UINTA COUNTY BURNS FIELD							DATED 12/21/2006		

TL 07-26 Pub 1-17-08

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FBR VOR/DME VIA AIRWAY RADIALS 213 CW 285.

*LNAV ONLY

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LPV ALL CATS VISIBILITY TO 1, LNAV/VNAV CAT D TO 1
AND LNAV CAT D TO 1 1/4

CITY AND STATE

EVANSTON, WY

ELEVATION: 7143 TDZE: 7143

AIRPORT NAME:

EVANSTON-UINTA COUNTY BURNS FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

RNAV (GPS) RWY 23, AMDT 4

JAN 17 2008

SUP:

AMDT: 3

DATED: 12/21/2006



U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

OPERATION TYPE
SBAS SERVICE PROVIDER IDENTIFIER
AIRPORT IDENTIFIER
RUNWAY
APPROACH PERFORMANCE DESIGNATOR
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR
REFERENCE PATH IDENTIFIER (APPROACH ID)
LTP/FTP LATITUDE
LTP/FTP LONGITUDE
LTP/FTP ELLIPSOIDAL HEIGHT
FPAP LATITUDE
FPAP LONGITUDE
THRESHOLD CROSSING HEIGHT (TCH)
TCH UNITS SELECTOR (METERS OR FEET USED)
GLIDEPATH ANGLE (GPA)
COURSE WIDTH AT THRESHOLD
LENGTH OFFSET
HORIZONTAL ALERT LIMIT (HAL)
VERTICAL ALERT LIMIT (VAL)

DATA

0
0
KEVW
RW23
0
0
W23A
411643.4660N
1110120.7565W
+21601
411614.8300N
1110249.1800W
00046.8
F
03.00
106.75
0016
40.0
50.0

CRC REMAINDER

CDCF1DB2

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE
LTP ORTHOMETRIC HEIGHT
FPAP ORTHOMETRIC HEIGHT

K1
+21752
+21752

CITY AND STATE
EVANSTON, WY

ELEVATION: 7143 TDZE: 7143
AIRPORT NAME:
EVANSTON-JUNTA COUNTY BURNS FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 23, AMDT 4

JAN 17 2008

SUP:
AMDT: 3
DATED: 12/21/2006

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE EVANSTON, WY	ELEVATION: 7143 TDZE: 7143 AIRPORT NAME: EVANSTON-UINTA COUNTY BURNS FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 23, AMDT 4 JAN 17 2008	SUP:
				AMDT: 3
				DATED: 12/21/2006



Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

PAGE 5 OF 6 PAGES