

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**VOR STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
EDITS INT/PDZ VORTAC 12.00 DME	RAL VOR	275.21 / 8.45	5500	MAP: 6.90 MILES AFTER RIVYO INT
SBD NDB	RAL VOR	200.56 / 7.36	5000	CLIMB TO 2800 THEN CLIMBING RIGHT TURN TO 4600 DIRECT PDZ VORTAC AND HOLD.
PDZ VORTAC	RIVYO INT	296.12 / 3.97	4500	
RAL VOR	RIVYO INT	259.32 / 7.00	4500	
				<b>ADDITIONAL FLIGHT DATA:</b> HOLD E, RT, 269.00 INBOUND. FAS OBST: 1719 AAO 335645N/1173103W RIVYO TO RW09: 3.68/41 FAC CROSSES RWY C/L EXTENDED 3020 FROM THLD.

1. PT L SIDE OF COURSE 259.32 OUTBOUND 4500 FT WITHIN 10 MILES OF RIVYO INT (IAF)
- 2.
3. FAC 079.32 FAF RIVYO INT DIST FAF TO MAP 6.90 THLD 6.90
4. MIN. ALT RIVYO INT 3500
8. MSA FROM: RAL VOR 030-120 11900, 120-210 7000, 210-030 11300

MAG VAR: 14E EPOCH YEAR:2000

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A			#		
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-9	2020	1 1/4	1260	2020	1 1/2	1260	2020	3	1260						
CIRCLING	2020	1 1/4	1201	2020	1 1/2	1201	2020	3	1201						

**NOTES:**  
 CHART NOTE: CIRCLING TO RWY 16 NA AT NIGHT.  
 CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 34 NA AT NIGHT.  
 CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 09 PROCEDURE NA AT NIGHT.  
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
 (SEE FORM 8260-10)

# CAT A, B 1300-2, CAT C 1300-3  
 # NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY  
1  
CHECKED

CITY AND STATE RIVERSIDE, CA	ELEVATION: 819	THRE: 760	FACILITY IDENTIFIER: RAL	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
	AIRPORT NAME:  RIVERSIDE MUNI			VOR RWY 9, AMDT 1 20 SEPTEMBER 2012	AMDT ORIG
					DATE 03/12/2009

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):**

**CHART PROFILE NOTE: VGS1 AND DESCENT ANGLES NOT COINCIDENT.**

**CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHINO ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET.**



CITY AND STATE RIVERSIDE, CA	ELEVATION: 819      THRE: 760	FACILITY IDENTIFIER: RAL	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 9, AMDT 1 20 SEPTEMBER 2012	SUP:
	AIRPORT NAME: RIVERSIDE MUNI			AMDT:      ORIG
				DATED:      03/12/2009