

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

NDB STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
OLLAS INT	RUE NDB	000.33/15.39	3000

MAP: RUE NDB

CLIMB TO 3000 THEN RIGHT TURN DIRECT RUE NDB AND HOLD,

ADDITIONAL FLIGHT DATA:
 HOLD S, RT, 360.00 INBOUND
 FAS OBST: 670 TREES 351400/0930543

1. PT L SIDE OF COURSE 180.32 OUTBOUND 2500 FT WITHIN 10 MILES OF RUE NDB (IAF)
2. _____
3. FAC 000.32 FAF _____ DIST FAF TO MAP - THLD -
4. MIN. ALT _____
8. MSA FROM: RUE NDB 4000

MAG VAR: 3E EPOCH YEAR: 95

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N		A	X			
CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	1140	1	737	1140	1	737	1140	2	737	1220	2 3/4	817			

NOTES:

CITY AND STATE RUSSELLVILLE, AR	ELEVATION: 403 TDZE:	FACILITY IDENTIFIER: RUE	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: NDB-A, AMDT 4B	SUP
	AIRPORT NAME: RUSSELLVILLE RGNL			AMDT 4A
				DATE 11/01/95