

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.	HOLD SE MAI VORTAC, LT, 316.15 INBOUND, 2000 FT. IN LIEU OF PT (IAF)				
3. FAC	316.15	FAF MAI VORTAC	DIST FAF TO MAP		3.96 THLD
4. MIN. ALT	MAI VORTAC 1800				
8. MSA FROM:	MAI VORTAC 2500				
					MAG VAR: 0E EPOCH YEAR: 1980

NOTES:

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BAINBRIDGE ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
5
CHECKED

FAA FORM 8260-5 / December 2002 (computer generated)