

U.S. Department
of Transportation

800 Independence Ave., S.W.
Washington D.C. 20591

**Federal Aviation
Administration**

Transmittal Letter 20-09

March 6, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as
follows:

.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/23/2020	FL	Marianna	Marianna Muni	0/9684	2/26/2020	VOR-A, Amdt 12A

AIRAC Date: 23 APRIL 2020

FDC 0/9684 MAI IAP MARIANNA MUNI, MARIANNA, FL. VOR-A, AMDT 12A... CHART CIRCLING ICON. CIRCLING
CAT A/B MDA 620/HAA 510. CAT D MDA 900/HAA 790. CIRCLING CAT D VISIBILITY 2 1/2. DELETE NOTE: NIGHT
LANDING RWY 26 NA. CHART NOTE: CIRCLING RWY 26 NA AT NIGHT. ALTERNATE MINIMUMS STANDARD
EXCEPT CAT D 800-2 1/2. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BAINBRIDGE
ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT
RECEIVED, USE BAINBRIDGE ALTIMETER SETTING; INCREASE ALL MDA 80 FEET AND CIRCLING CAT D VISIBILITY
1/4 SM. THIS IS VOR-A, AMDT 12B. 2002261609-PERM