

**Federal Aviation
Administration**

Transmittal Letter 22-17

June 24, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/11/2022	IL	Champaign / Urbana	University Of Illinois/Willard	2/9696	5/9/2022	RNAV (GPS) RWY 22, Amdt 1A

AIRAC Date: 11 AUGUST 2022

FDC 2/9696 CMI IAP UNIVERSITY OF ILLINOIS/WILLARD, CHAMPAIGN/URBANA, IL. RNAV (GPS) RWY 22, AMDT 1A... DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -22C OR ABOVE 54C. DELETE NOTE: *VDP 1 NM TO RW22. CHART VDP 1.03 NM TO RW22. DELETE ASTERISK FROM MINIMUM ALTITUDE AT JESDI 1460. DELETE NOTE: * LNAV ONLY. CHART FAS OBST: 864 TOWER (17-030825) 400403N/0881454W. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE RANTOUL ALTIMETER SETTING AND INCREASE LPV DA TO 1041 FEET AND ALL VISIBILITIES 1/8 SM. INCREASE LNAV/VNAV DA TO 1260 FEET; INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C/D 1/4 SM, AND CIRCLING VISIBILITY CAT D 1/4 SM. ALTERNATE MINIMUMS: STANDARD - EXCEPT CAT C/ D 800-2 1/4- NA WHEN LOCAL WEATHER NOT AVAILABLE. LPV ALL CATS VIS 3/4, LNAV/VNAV ALL CATS VIS 1 3/8. LNAV ALL CATS VIS 1. CIRCLING CAT D VIS 2 1/4. CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 22, AMDT 1B. 2205051729-PERM