

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SANFORD	ONE	SFB1.SFB	NINE	04/07/2021	2 DEC 2021

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	☐	☐	☒	☐	☐

DP ROUTE DESCRIPTION:

TAKEOFF RWY 9R: CLIMB ON HEADING 094.92, THENCE ...
 TAKEOFF RWY 9C: CLIMB ON HEADING 094.90, THENCE ...
 TAKEOFF RWY 9L: CLIMB ON HEADING 094.87, THENCE ...
 TAKEOFF RWY 27R: CLIMB ON HEADING 274.90, THENCE ...
 TAKEOFF RWY 27C: CLIMB ON HEADING 274.91, THENCE ...
 TAKEOFF RWY 27L: CLIMB ON HEADING 274.92, THENCE ...
 TAKEOFF RWY 18: CLIMB ON HEADING 184.88, THENCE ...
 TAKEOFF RWY 36: CLIMB ON HEADING 004.88, THENCE ...

... EXPECT VECTORS TO APPROPRIATE FIX. MAINTAIN 2000. EXPECT FURTHER CLEARANCE TO FILED ALTITUDE/FLIGHT LEVEL TEN (10) MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:

NOTE: RADAR REQUIRED

TAKEOFF MINIMUMS:

TAKEOFF MINIMUMS: RWY 9R, 9C, 9L, 27R, 27C, 27L, 18, 36 STANDARD

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:**LOST COMMUNICATIONS PROCEDURES:****ADDITIONAL FLIGHT DATA:**

REFERENCE MAG VAR: KSFB 5W EPOCH YEAR: 2000

CHART: TOP ALTITUDE: 2000

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
ORLANDO SANFORD INTL	KSFB	ORLANDO	FL

COMMUNICATIONS:

SFB ATIS, SFB CLNC DEL, ORL CLNC DEL (WHEN TOWER CLOSED), ORL DEP CON

QUALITY
45
CHECKED

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SANFORD	ONE	SFB1.SFB	NINE	04/07/2021	2 DEC 2021

FIXES AND/OR NAVAIDS:

SZW VORTAC. CRG VORTAC, OCF VORTAC, OMN VORTAC, ORL VORTAC, MLB VOR/DME, PIE VORTAC, LAL VORTAC, SRQ VOR/DME, RSW VORTAC, PBI VORTAC.

REMARKS:

ABBREVIATED AMENDMENT.

FLIGHT INSPECTED BY

PROCESSED IAW AIRCRADT OPERATIONS GROUP (AJF-10) MEMO, APRIL 29, 2020
SUBJECT: FLIGHT INSPECTION REVIEW NOT REQUIRED.

Digitally signed by

DAVID TEFFETELLER

Jun 09, 2021

OFFICE

DATE

DEVELOPED BY

DAVID TEFFETELLER (CASEY HILL)

Digitally signed by

DAVID TEFFETELLER

Jun 09, 2021

OFFICE

DATE

AJV-A432

06/03/2021

APPROVED BY

LONNIE EVERHART

Digitally signed by

DAVID TEFFETELLER

Jun 09, 2021

OFFICE

DATE

AJV-A430

TITLE

MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A ☒

ALPA ☒

AOPA ☒

APA ☐

HAI ☐

NBAA ☒

OTHER: ZJX, MCO APP CON, SF ATCT, ARPT MGR

CHANGES - REASONS:

1. CORRECTED RWY 38 TO RWY 36 IN DP ROUTE DESCRIPTION- RWY NUMBER CORRECTION.