

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> BELLEVILLE MUNI	<u>AIRPORT ID</u> KRPB	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 36	<u>ORIGINAL/AMENDMENT</u> ORIG-C	<u>CITY</u> BELLEVILLE	<u>STATE</u> KS
<u>AIRPORT ELEVATION</u> 1538	<u>TDZE</u> 1538	<u>SUPERSEDED</u> RNAV (GPS) RWY 36	<u>ORIGINAL/AMENDMENT</u> ORIG-B	<u>DATED</u> 11/10/2016	<u>MAG VAR</u> 7E
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 16 JULY 2020	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>	<u>EPOCH YEAR</u> 1985

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
SLN VORTAC	IAF	ZANPU		TF	FB	1.00	350.12	42.03	3400
ZANPU	IF	YISYU		TF	FB	1.00	354.51	6.20	3200
YISYU	FAF	UMHOY/1.90 NM TO RW36		TF	FB	0.30	354.51	3.19	
UMHOY/1.90 NM TO RW36		RW36	MAP	TF	FO	0.30	354.51	1.90	
RW36	MAP	1920 MSL		CA			354.51		
1920 MSL		FEBNO		DF	FO	1.00			3400

MISSED APPROACH

MAP:

LP: RW36
LNAV: RW36

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3400 DIRECT FEBNO AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. PROFILE STARTS AT ZANPU

3. FAC: 354.51 FAF: YISYU DIST FAF TO MAP: 5.09 DIST FAF TO THLD: 5.09

4. MIN ALT: ZANPU 3400, YISYU 3200, UMHOY/1.90 NM TO RW36 2180

5. DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: MM: IM:

6. MIN GP INCPT: GP ALT AT FAF : OM: MM: IM:

7. GP ANGLE: 34:1: IS CLEAR 20:1: IS CLEAR TCH:

8. MSA FROM: RW36 3900

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: CIRCLING NA TO RWYS 14 AND 32.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON SLN VORTAC AIRWAY RADIALS 273 CW 075.
CHART NOTE: USE CONCORDIA ALTIMETER SETTING.

ADDITIONAL FLIGHT DATA:

CHART CONCORDIA ASOS-3.
YISYU TO RW36: 3.00/40.6.
WAAS CHANNEL #69425
REFERENCE PATH ID: W36A
CHART FAS OBST: 1615 TREE 394706N/0974000W, 1625 TREE 394737N/0974001W.
HOLD N, RT, 174.51 INBOUND
LTP HAE: 442.1 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LP MDA	1920	1	382	1920	1	382	1920	1 1/8	382		NA				
LNAV MDA	1920	1	382	1920	1	382	1920	1 1/8	382		NA				
CIRCLING	2040	1	502	2040	1	502	2040	1 1/2	502		NA				

CHANGES - REASONS

1. PREVIOUSLY CHARTED CHANGES FROM P-NOTAM ACTIONS FOR AMENDMENTS ORIG-B HAVE BEEN INCORPORATED ON THIS FORM.
2. PROFILE LINE 7: UPDATED 34:1 FROM "IS NOT CLEAR" TO "IS CLEAR" AND ADDED 20:1 IS CLEAR - IAW 8260.19H 8-6-7G.
3. REMOVED ALL NOTES REFERENCING BACK-UP ALTIMETER SETTING - PRIMARY ASOS ON WMSCR, ADJUSTMENTS MOVED TO FORM 8260-9 FOR CONTINGENCY USE.
4. REMOVED CHART NOTE "DME/DME RNP-0.3 NA" AND ADDED "RNP APCH" IN PBN REQUIREMENT NOTES - UPDATE TO CURRENT CRITERIA IAW 8260.19H 8-6-8.B.(1).
5. UPDATED CIRCLING CMDA/HAA FOR ALL CATEGORIES FROM "2020/482" TO "2040/502" - NEW CONTROLLING OBSTACLES.
6. ADDITIONAL FLIGHT DATA: ADDED "CHART CONCORDIA ASOS-3" - IAW 8260.19H 8-2-4B(3).



COORDINATED WITH:

A4A ☐ **ALPA** ☒ **AOPA** ☒ **APA** ☐ **HAI** ☐ **NBAA** ☒ **OTHER:** ZMP, AMGR

FLIGHT CHECKED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE

DATE

DEVELOPED BY

DONALD H. LANIER (CHRISTOPHER SCHONES)

Digitally signed by

DONALD H LANIER

DONALD H LANIER

Mar 26, 2020

OFFICE

AJV-A431

DATE

12/30/2019

APPROVED BY

GEORGE DAVIS

Digitally signed by

DONALD H LANIER

Mar 26, 2020

OFFICE

AJV-A430

DATE

TITLE

MANAGER



FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRPB
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	394848.9000N
LTP/FTP LONGITUDE	0973937.7600W
LTP/FTP ELLIPSOIDAL HEIGHT	+04421
FPAP LATITUDE	395018.0400N
FPAP LONGITUDE	0973934.7100W
THRESHOLD CROSSING HEIGHT (TCH)	00040.6
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1680
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
CRC REMAINDER	C8A1ABF1

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+04688
FPAP ORTHOMETRIC HEIGHT	+04688

