

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LNAV: RW36 CLIMB TO 3800 DIRECT WODIR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 176.04 INBOUND. CHART FAS OBST: 1574 TREE 304328N/0991114W CHART CIRCLING ICON. JUTGU TO RW36: 3.00/40. CHART BRADY AWOS-3.								
UCOBA (IF/IAF)		JUTGU (TF) (FB) (RNP 1.00)		356.04 / 6.19			3100										
JUTGU (FAF)		EWETO/2.50 NM TO RW36 (TF) (FB) (RNP 0.30)		356.04 / 2.40													
EWETO/2.50 NM TO RW36		RW36 (MAP) (TF) (FO) (RNP 0.30)		356.04 / 2.50													
RW36 (MAP)		1914 MSL (CA)		356.04													
1914 MSL		WODIR (DF) (FO) (RNP 1.00)					3800										
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S UCOBA, RT, 356.04 INBOUND, 3800 FT. IN LIEU OF PT (IAF) 3. FAC: 356.04 FAF: JUTGU DIST FAF TO MAP: 4.90 THLD: 4.90 4. MIN. ALT: UCOBA 3800, JUTGU 3100, EWETO/2.50 NM TO RW36 2320 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____										MAG VAR: 5E		EPOCH YEAR: 2015					
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		☒ X					
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LNAV MDA	1940	1	442	1940	1	442		NA			NA						
CIRCLING	2140	1	626	2140	1	626		NA			NA						
NOTES: CHART NOTE: RWY 18/36 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: USE BRADY ALTIMETER SETTING; WHEN NOT RECEIVED, USE LLANO ALTIMETER SETTING AND INCREASE ALL MDAS 20 FEET.																	
CITY AND STATE		ELEVATION: 1514 TDZE: 1498			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:						SUP:				
MASON, TX		AIRPORT NAME: MASON COUNTY					RNAV (GPS) RWY 36, ORIG-C 17 AUGUST 2017						AMDT: ORIG-B				
													DATED 04/02/2015				



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	286/30 CW 066/30 (NOPT)	UCOBA (IF/IAF) (FB)	3800
2.	066/30 CW 286/30	UCOBA (IF/IAF) (FO)	3800

QUALITY
4
CHECKED

CITY AND STATE MASON, TX	ELEVATION: 1514 TDZE: 1498 AIRPORT NAME: MASON COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG-C 17 AUGUST 2017	SUP:
				AMDT: ORIG-B
				DATED: 04/02/2015