

## U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

NDB

## STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in foot RVR.

## TERMINAL ROUTES

## MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: SDR NDB
LORAN INT	SDR NDB	308.73/21.69	4100	CLIMBING LEFT TURN TO 4100 IN SDR NDB HOLDING PATTERN
WEEPE INT	SDR NDB	009.28/18.07	4100	
THIS IS A CORRECTED COPY OF A PROCEDURE PUBLISHED IN TL 03-13.				ADDITIONAL FLIGHT DATA: HOLD S, LT, 358.32 INBOUND FAS OBST: 2555 RIG 324100/1005531 CHART: TDZE 2426 FAC CROSSES RWY C/L EXTENDED 3008 FROM THLD

1. PT R SIDE OF COURSE 178.32 OUTBOUND 4100 FT WITHIN 10 MILES OF SDR NDB (IAF)  
 2. \_\_\_\_\_  
 3. FAC 358.32 FAF \_\_\_\_\_ DIST FAF TO MAP \_\_\_\_\_ THLD \_\_\_\_\_  
 4. MIN. ALT \_\_\_\_\_  
 8. MSA FROM: SDR NDB 4300

MAG VAR: 8E

EPOCH YEAR: 90

## MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		X						
CATEGORY		A			B			C			D			E				
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA		
S-35		2960	1	534	2960	1	534	2960	1 1/2	534		NA						
CIRCLING		2960	1	530	2960	1	530	2960	1 1/2	530		NA						

## NOTES:

CIRCLING NA TO RWY 8/26

TL 03-14

CITY AND STATE	ELEVATION: 2430 TDZE: 2426	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP
SNYDER, TX	AIRPORT NAME: WINSTON FIELD	SDR	NDB RWY 35, AMDT 2	AMDT 1
			JUL 10 2003	DATE 9/21/89