

**Federal Aviation
Administration**

Transmittal Letter 21-15

MAY 28, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/15/2021	MN	Litchfield	Litchfield Muni	1/4703	4/23/2021	RNAV (GPS) RWY 13, Orig

Airac Date: 15 JULY 2021

FDC 1/4703 LJF IAP LITCHFIELD MUNI, LITCHFIELD, MN. RNAV (GPS) RWY 13, ORIG...
CIRCLING CAT C MDA 1860/HAA 720, CAT D MDA 2080/HAA 940, VISIBILITY CAT D 3.
CHANGE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS,
LNAV/VNAV NA BELOW -17C OR ABOVE 54C. CHANGE NOTE TO READ: WHEN LOCAL
ALTIMETER SETTING NOT RECEIVED, USE HUTCHINSON ALTIMETER SETTING:
INCREASE LPV DA TO 1436 FEET; INCREASE LNAV/VNAV DA TO 1980 FEET AND
VISIBILITY ALL CATS 1/4 SM; INCREASE ALL MDA 60 FEET AND CIRCLING CAT C
VISIBILITY 1/4 SM. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE:
RNP APCH - GPS. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 1000-3; NA WHEN
LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 13, ORIG-A. 2104231343-
PERM