

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
HALKI (IF/IAF)	ZIRET (FB)	094.88 / 6.90	2400	LNAV: RW10
ZIRET (FAF)	WUXUL/2.10 NM TO RW10 (FB)	095.00 / 3.18		CLIMB TO 2600 DIRECT DUCER AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 275.31 INBOUND. CHART FAS OBST: 799 TREE 455900N/0861127W ZIRET TO RW10: 3.00/35.
WUXUL/2.10 NM TO RW10	RW10 (MAP) (FO)	095.05 / 2.10		
RW10 (MAP)	1060 MSL	095.05		
1060 MSL	DUCER (FO)		2600	

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD W HALKI, RT, 094.88 INBOUND, 2600 FT. IN LIEU OF PT (IAF)
3. FAC: 095.00 FAF: ZIRET DIST FAF TO MAP: 5.28 THLD: 5.28
4. MIN. ALT: HALKI 2600, ZIRET 2400, WUXUL/2.10 NM TO RW10 1380
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM:

MAG VAR: 5W EPOCH YEAR: 1995

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A			STANDARD @		
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1060	1	376	1060	1	376	1060	1	376	1060	1	376			
CIRCLING	1120	1	436	1140	1	456	1140	1 1/2	456	1260	2	576			

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BEAVER ISLAND ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET, INCREASE LNAV CAT C AND D VISIBILITY 3/8 MILE.
 (SEE FORM 8260-10)



CITY AND STATE MANISTIQUE, MI	ELEVATION: 684 THRE: 684 AIRPORT NAME: SCHOOLCRAFT COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10, ORIG 3 MAY 2012	SUP: AMDT: NONE DATED
----------------------------------	--	------------------------------	---	-----------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 10 PROCEDURE NA AT NIGHT.

CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 28 NA AT NIGHT.

CHART NOTE: CIRCLING TO RWY 1/19 NA AT NIGHT.

TAA

	FROM	TO	ALT
1.	005/30 CW 185/30 (NOPT)	005/10 CW 185/10	3100
2.	005/10 CW 185/10	HALKI (IF/IAF) (FB)	2600
3.	185/30 CW 005/30	HALKI (IF/IAF) (FO)	2600



CITY AND STATE MANISTIQUE, MI	ELEVATION: 684	THRE: 684	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10, ORIG 3 MAY 2012	SUP:
	AIRPORT NAME: SCHOOLCRAFT COUNTY				AMDT: NONE
					DATED:

