

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

1. PT	L	SIDE OF COURSE	059.58	OUTBOUND	1800	FT WITHIN	10	MILES OF	ACK VOR/DME	(IAF)
2.										
3. FAC	239.58	FAF	ACK VOR/DME			DIST FAF TO MAP	1.91	THLD	1.91	
4. MIN. ALT	ACK VOR/DME	800								
8. MSA FROM:	ACK VOR/DME	1700								

MAG VAR: 15W
EPOCH YEAR: 1980

NOTES:	
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.	@ NA WHEN LOCAL WEATHER NOT AVAILABLE.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HYANNIS ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET; INCREASE S-24 CAT C VISIBILITY TO RVR 4000.	
CHART NOTE: VDP NA WHEN USING HYANNIS ALTIMETER SETTING.	
CHART NOTE: FOR INOPERATIVE SSALR, INCREASE S-24 CAT D VISIBILITY TO RVR 6000.	

FAA FORM 8260-5 / December 2002 (computer generated) PAGE 1 OF 1 PAGES