08/06/2024

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE

GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAME NUMBER **DP COMPUTER CODE** SUPERSEDED NUMBER DATED ACTUAL EFFECTIVE DATE 31 OCT 24 ORELE ONE **ORELE1.ORELE** NONE TYPE: OBSTACLE COPTER SID SPECIAL RNAV \times \times

DP ROUTE DESCRIPTION:

TAKEOFF RWY 35: CLIMB ON HEADING 354.80 TO 4544, THEN CLIMBING LEFT TURN DIRECT BRKWY, CROSS BRKWY AT OR ABOVE 6000 AND AT OR BELOW 210 KIAS, THEN RIGHT TURN DIRECT LOWSE, THEN ON TRACK 139.03 TO MEWLS, CROSS MEWLS AT OR ABOVE 9900, THEN ON TRACK 170.99 TO NUBIE AND ON TRACK 111.22 TO ORELE, CROSS ORELE AT OR ABOVE 13600. MAINTAIN ATC ASSIGNED ALTITUDE. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

TRANSITION NAME	TRANSITION COMPUTER CODE	<u>FROM</u> <u>FIX/NAVAID</u>	<u>TO</u> <u>FIX/NAVAID</u>	COURSE	DISTANCE MEA	MOCA	CROSSING ALTITUDE/FIXES
-----------------	-----------------------------	----------------------------------	--------------------------------	--------	--------------	------	----------------------------

PBN REQUIREMENT NOTES:

RNAV 1 - GPS

EQUIPMENT REQUIREMENT NOTES:

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 17: NA - OBSTACLES RWY 35: 700-3 WITH MINIMUN CLIMB OF 470 FT/NM TO 8500.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

RWY 35: 4646 FT MSL VEGETATION 450927.00N/1135218.00W (CEILING), 4229 FT MSL VEGETATION 451012.00N/1135118.00W (VISIBILITY), 7376 FT MSL AAO 451321.00N/1134324.00W (CLIMB GRADIENT/CLIMB-TO ALTITUDE)

MSA:

MSA FROM KSMN 12200

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: UNSAT CHART: TOP ALTITUDE: ASSIGNED BY ATC. CHART SPEED ICON AT BRKWY: MAX 210 KIAS. CHART: MAXIMUM AIRCRAFT CATEGORY: CAT C AIRPORT MV: KSMN (P) 13E/2020

NFDD No 151		08/06/2024			17
DP NAME ORELE	NUMBER ONE	DP COMPUTER CODE ORELE1.ORELE	SUPERSEDED NUMBER NONE	DATED	ACTUAL EFFECTIVE DATE 31 OCT 24
AIRPORTS SERVED:					
AIRPORT ID		<u>CITY</u>			STATE
KSMN		SALMON			ID
COMMUNICATIONS: CHART: ZLC, BOISE RADIO					
FIXES AND/OR NAVAIDS:					
REMARKS:AIRPORT NVG SURVEY ESTABLISHED AS BV SURVEY.200 FT VEGETATION UTILILZED PER FPT.SEE AND AVOID WITH CG/CGTA REQUIRED DUE TO OBSTACLES.VA/DF APPLIED WITHOUT LNAV ENGAGEMENT CG DUE TO OBSTACLE CG/CFLIGHT INSPECTED BYSIGNATURE	GTA PROVIDES Digitally sign		OFFICE	DATE	
TROY E DEVINE	CASIMIR L TA Jun 07, 20	ABAKA	FPO	06/06/2024	
DEVELOPED BY Digitally signed by SIGNATURE			OFFICE	DATE	
KELLY DEAN KELLY D DEAN May 03, 2024			AJV-A432	11/30/2023	
APPROVED BY Digitally signed by SIGNATURE CAS TABAKA May 07, 2024			OFFICE AJV-A432	DATE	TITLE MANAGER
REQUIRED EFFECTIVE DATE ROUTINE					
COORDINATED WITH:					
A4A ALPA AOPA APA HAI NBAA CHANGES - REASONS:	OTHER: ZLC, S	STATE AERO DIV, AMGR			

05/03/2024 THIS IS A UPDATED COPY OF THE FORM DEVELOPED ON 11/30/2023 UPDATED DP ROUTE DESCRIPTION TO INCLUDE FULL ROUTING AND AT/ABOVE ALTITUDES AT MEWLS AND ORELE. ADDED AT/ABOVE ALTITUDES TO MEWLS AND ORELE ON 8260-15C. REMOVED MEWLS AND NUBIE FROM FIXES AND/OR NAVAIDS BLOCK.



NFDD No 151

08/06/2024

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE DEPARTURE (DATA RECORD)

DEPARTORE (DATA RECORD)											
DP NAME						NUMBER	DP COMPUTER C		SEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
ORELE						ONE	ORELE1.OREL	_E	NONE		31 OCT 24
FIX/NAVAID	LAT/LONG	<u>C</u>	FO/FB	<u>LEG</u> <u>TYPE</u>	<u>TC</u>	<u>DIST</u> (NM)	ALTITUDE	SPEED		REMARKS	
RWY35 (AER)	450656.89N/1135258.37W	Ν	-	-	-	-					
4544 MSL	-	-	-	VA	007.80	-	AT/ABOVE 4544			470 FT/NM TO 850 LEFT TURN	00
BRKWY	451148.64N/1135319.93W	Y	FO	DF	-	-	AT/ABOVE 6000	AT/BELOW 210		RIGHT TURN	
LOWSE	450400.86N/1134031.68W	Y	FB	DF	-	-					
MEWLS	445819.37N/1133616.30W	Y	FB	TF	152.03	6.44	AT/ABOVE 9900				
NUBIE	444744.45N/1133718.53W	Y	FB	TF	183.99	10.61					
ORELE	444002.96N/1132129.99W	Υ	FB	TF	124.22	13.64	AT/ABOVE 13600				