

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: AIR 19.14 DME FIX					
AIR VOR/DME (IF/IAF)		HOUSR/AIR 14.00 DME			229.46 / 14.00			3000		CLIMB TO 3000 THEN LEFT TURN ON AIR VOR/DME R-229.46 TO HOUSR/AIR 14.00 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 229.46 INBOUND. CHART FAS OBST: 1399 TREE 394939N/0810511W ZESRU TO RW25: 3.35/40. CHART CIRCLING ICON.					
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)														MAG VAR: 7W EPOCH YEAR: 1990	
2. PROFILE STARTS AT AIR VOR/DME <u> </u>															
3. FAC <u>229.46</u> FAF HOUSR/AIR 14.00 DME <u> </u> DIST FAF TO MAP <u> </u> THLD <u>5.14</u>															
4. MIN. ALT <u>AIR VOR/DME 3000, HOUSR 3000, ZESRU/AIR 17.20 DME 1920</u>															
8. MSA FROM: AIR VOR/DME 3400															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X					
CATEGORY >>>>>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-25	1740	1	550	1740	1	550	1740	1 5/8	550		NA				
CIRCLING	1860	1	663	1860	1	663	1860	1 3/4	663		NA				
NOTES: CHART NOTE: USE WHEELING OHIO CO, WV ALTIMETER SETTING; WHEN NOT RECEIVED USE PARKERSBURG, WV ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET; INCREASE S-25 CAT C VISIBILITY 1/8 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHART NOTE: PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)															
CITY AND STATE WOODSFIELD, OH				ELEVATION: 1197 THRE: 1190 AIRPORT NAME: MONROE COUNTY				FACILITY IDENTIFIER: AIR		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 25, AMDT 7 14 NOVEMBER 2013				SUP VOR/DME OR GPS RWY 25 AMDT 6 DATE 08/20/1992	

QUALITY
 3
 CHECKED

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON AIR VOR/DME AIRWAY RADIALS 224 CW 272.



CITY AND STATE

WOODSFIELD, OH

ELEVATION: 1197

THRE: 1190

AIRPORT NAME:

MONROE COUNTY

FACILITY
IDENTIFIER:

AIR

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR/DME RWY 25, AMDT 7
14 NOVEMBER 2013SUP: VOR/DME OR GPS
RWY 25

AMDT: 6

DATED: 08/20/1992