

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

*LNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EL DORADO ALTIMETER SETTING AND INCREASE ALL DA/MDA 80 FT, LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE AND LNAV CATS C AND D VISIBILITY 3/8 MILE.

CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 1 PROCEDURE NA AT NIGHT.

CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 19 NA AT NIGHT.

TAA

	FROM	TO	ALT
1.	298/30 CW 078/30 (NOPT)	URAME (IF/AF) (FB)	2700
2.	078/30 CW 298/30	URAME (IF/AF) (FO)	2700

QUALITY
1
CHECKED

CITY AND STATE

CAMDEN, AR

ELEVATION: 130

THRE: 123

AIRPORT NAME:

HARRELL FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 1, AMDT 1

31 MAY 2012

SUP: RNAV (GPS) RWY 36

AMDT: ORIG

DATED: 09/28/2006

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCDH
RUNWAY	RW01
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W01A
LTP/FTP LATITUDE	333650.3110N
LTP/FTP LONGITUDE	0924554.2810W
LTP/FTP ELLIPSOIDAL HEIGHT	+00112
FPAP LATITUDE	333818.4600N
FPAP LONGITUDE	0924537.4600W
THRESHOLD CROSSING HEIGHT (TCH)	00044.9
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0768
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

E3F9FE55

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00375
FPAP ORTHOMETRIC HEIGHT	+00375

QUALITY
CHECKED

CITY AND STATE CAMDEN, AR	ELEVATION: 130 THRE: 123 AIRPORT NAME: HARRELL FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, AMDT 1 31 MAY 2012	SUP. RNAV (GPS) RWY 36
				AMDT: ORIG
				DATED: 09/28/2006

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
CHECKED

CITY AND STATE CAMDEN, AR	ELEVATION: 130 THRE: 123 AIRPORT NAME: HARRELL FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, AMDT 1 31 MAY 2012	SUP: RNAV (GPS) RWY 36
				AMDT: ORIG
				DATED: 09/28/2006